Energizer.
Holdings Inc.

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

SECTION 1: Identification

1.1 Product identifier

Trade name Armor All Extreme Tire Shine - Aerosol

Alternative number(s) 070612779588

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc. 25225 Detroit Rd. Westlake OH 44145 United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)

e-mail: Autocare.regulatory@energizer.com

Website: http://data.energizer.com

1.4 Emergency telephone number

Emergency information service

FOR EMERGENCY in USA & Canada CALL +1 800 255-3924 / For International CALL +1 813 248 0585 This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
B.3	flammable aerosol	1	Flam. Aerosol 1	H222
B.5	gases under pressure	С	Press. Gas C	H280

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects Contains gas under pressure; may explode if heated.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

United States: en Page: 1 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

- Pictograms

GHS02, GHS04



- Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.
P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3 Other hazards

Hazards not otherwise classified

Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of \geq 0.1%.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of \geq 0.1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
isobutane	CAS No 75-28-5	1-<5	Flam. Gas 1 / H220 Press. Gas C / H280	
propane	CAS No 74-98-6	1-<5	sA / OSHA002 Flam. Gas 1 / H220 Press. Gas C / H280	

United States: en Page: 2 / 24



Replaces version of: 2022-07-05 (GHS 9)

acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
sodium nitrite	CAS No 7632-00-0	<1	Acute Tox. 3 / H301 Eye Irrit. 2 / H319 Ox. Sol. 2 / H272	
morpholine	CAS No 110-91-8	<1	Acute Tox. 4 / H302 Acute Tox. 3 / H311 Acute Tox. 4 / H332 Skin Corr. 1B / H314 Eye Dam. 1 / H318 Flam. Liq. 3 / H226	

For full text of abbreviations: see SECTION 16.

Legend: Press. Gas

Press. Gas C: Gas under pressure: compressed gas

Press. Gas L: Gas under pressure: liquefied gas

Press. Gas R: Gas under pressure: refrigerated liquefied gas

Press. Gas D: Gas under pressure: dissolved gas.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Thaw frosted parts with lukewarm water. Do not rub affected area.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

United States: en Page: 3 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Contact with the product can cause burns and/or frostbite. Contains gas under pressure; may explode if heated.

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

United States: en Page: 4 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

frost

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	morpholine	110-91-8	REL	20 (10 h)	70 (10 h)	30	105				NIOSH REL
US	morpholine	110-91-8	PEL	20	70						29 CFR 1910.1 000

United States: en Page: 5 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	morpholine	110-91-8	TLV®	20						Н	AC- GIH® 2023
US	morpholine (tet- rahydro-2H-1,4- oxazine)	110-91-8	PEL (CA)	20	70	30	105				Cal/ OSHA PEL
US	propane	74-98-6	PEL (CA)	1,000	1,800						Cal/ OSHA PEL
US	propane	74-98-6	REL	1,000 (10 h)	1,800 (10 h)						NIOSH REL
US	propane	74-98-6	PEL	1,000	1,800						29 CFR 1910.1 000
US	propane	74-98-6	TLV®							oxy- gen, Simpl e Asp., E	AC- GIH® 2023
US	isobutane	75-28-5	REL	800 (10 h)	1,900 (10 h)						NIOSH REL
US	isobutane	75-28-5	TLV®			1,000				E	AC- GIH® 2023

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

explosive

absorbed through the skin

Adequate oxygen delivery to the tissues is necessary for sustaining life oxygen

Simple Asp. simple asphyxiants

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period

(unless otherwise specified)

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified TWA

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
sodium nitrite	7632-00-0	DNEL	2 mg/m³	human, inhalatory	worker (industry)	chronic - systemic

United States: en Page: 6 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
						effects
sodium nitrite	7632-00-0	DNEL	2 mg/m³	human, inhalatory	worker (industry)	acute - systemic ef- fects
morpholine	110-91-8	DNEL	91 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
morpholine	110-91-8	DNEL	36 mg/m³	human, inhalatory	worker (industry)	chronic - local ef- fects
morpholine	110-91-8	DNEL	72 mg/m³	human, inhalatory	worker (industry)	acute - local effects
morpholine	110-91-8	DNEL	0.84 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
sodium nitrite	7632-00-0	PNEC	0.0054 ^{mg} / _l	aquatic organ- isms	water	intermittent re- lease
sodium nitrite	7632-00-0	PNEC	0.005 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.006 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	21 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.019 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.022 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.001 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
morpholine	110-91-8	PNEC	0.163 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
morpholine	110-91-8	PNEC	0.016 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
morpholine	110-91-8	PNEC	10 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)

United States: en Page: 7 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
morpholine	110-91-8	PNEC	1.83 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
morpholine	110-91-8	PNEC	0.183 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
morpholine	110-91-8	PNEC	0.269 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	aerosol (spray aerosol)
Color	not determined
Particle	not relevant (aerosol)

United States: en Page: 8 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

es version of: 2022-07-05 (GHS 9)	
Odor	characteristic
Other safety parameters	<u>-</u>
pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	-161.5 °C at 1,013 hPa
Flash point	-88.6 °C at 1,013 hPa
Evaporation rate	Not determined
Flammability (solid, gas)	flammable aerosol in accordance with GHS criteria
Explosive limits	
- Lower explosion limit (LEL)	5 vol%
- Upper explosion limit (UEL)	15 vol%
Vapor pressure	not determined
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	>410 °C (auto-ignition temperature (liquids and gases))
Viscosity	not relevant (aerosol)
Explosive properties	none
Oxidizing properties	none

United States: en Page: 9 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

9.2 Other information

Propellant content	9 %
Temperature class (USA, acc. to NEC 500)	T2 (maximum permissible surface temperature on the equipment: 300°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Gas under pressure. Risk of ignition.

If heated:

Danger of explosion, Gas under pressure, Danger of bursting container

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

United States: en Page: 10 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
sodium nitrite	7632-00-0	oral	100 ^{mg} / _{kg}
morpholine	110-91-8	oral	1,900 ^{mg} / _{kg}
morpholine	110-91-8	dermal	500 ^{mg} / _{kg}
morpholine	110-91-8	inhalation: vapor	11 ^{mg} / _l /4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
morpholine	110-91-8	3	

Legend

3

Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

United States: en Page: 11 / 24





Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
isobutane	75-28-5	LC50	49.9 ^{mg} / _l	fish	96 h
isobutane	75-28-5	EC50	19.37 ^{mg} / _l	algae	96 h
propane	74-98-6	LC50	49.9 ^{mg} / _l	fish	96 h
propane	74-98-6	EC50	19.37 ^{mg} / _l	algae	96 h
sodium nitrite	7632-00-0	LC50	26.3 ^{mg} / _l	fish	96 h
sodium nitrite	7632-00-0	EC50	15.4 ^{mg} / _l	aquatic invertebrates	48 h
sodium nitrite	7632-00-0	ErC50	>100 ^{mg} / _l	algae	72 h
sodium nitrite	7632-00-0	NOEC	100 ^{mg} / _l	algae	72 h
morpholine	110-91-8	LC50	>100 ^{mg} / _l	fish	96 h
morpholine	110-91-8	EC50	44.5 ^{mg} / _l	aquatic invertebrates	48 h
morpholine	110-91-8	ErC50	64.63 ^{mg} / _l	algae	72 h
morpholine	110-91-8	NOEC	18.8 ^{mg} / _l	aquatic invertebrates	48 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
sodium nitrite	7632-00-0	EC50	114.9 ^{mg} / _l	aquatic invertebrates	80 d
sodium nitrite	7632-00-0	LC50	>95.6 ^{mg} / _l	aquatic invertebrates	80 d
sodium nitrite	7632-00-0	NOEC	21 ^{mg} / _l	fish	29 d
morpholine	110-91-8	EC50	12.19 ^{mg} / _l	aquatic invertebrates	21 d
morpholine	110-91-8	NOEC	5 ^{mg} / _l	aquatic invertebrates	21 d

12.2 Persistence and degradability

Data are not available.

United States: en Page: 12 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

12.3 Bioaccumulative potential

The substance fulfills the very bioaccumulative criterion.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of \geq 0.1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 1950
IMDG-Code	UN 1950
ICAO-TI	UN 1950

14.2 UN proper shipping name

DOT	Aerosols
IMDG-Code	AEROSOLS

ICAO-TI Aerosols, flammable

14.3 Transport hazard class(es)

DOT	2.1
IMDG-Code	2.1

United States: en Page: 13 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

ICAO-TI 2.1

14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the danger-

ous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

DOT

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration UN1950, Aerosols, 2.1

Reportable quantity (RQ) 14,641 lbs (6,647 kg) (sodium nitrite) (cyclohexane)

Danger label(s) 2.1



Special provisions (SP) N82 **ERG No** 126

International Maritime Dangerous Goods Code (IMDG) - Additional information

UN1950, AEROSOLS, 2.1, -88.6°C c.c. Particulars in the shipper's declaration

Marine pollutant Danger label(s) 2.1



Stowage category

Special provisions (SP) 63, 190, 277, 327, 344, 381, 959

Excepted quantities (EQ) E0 Limited quantities (LQ) 1 L **EmS**

F-D, S-U

United States: en Page: 14 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Particulars in the shipper's declaration UN1950, Aerosols, flammable, 2.1

Danger label(s) 2.1



Special provisions (SP) A145, A167

Excepted quantities (EQ) E0
Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed (ACTIVE) or exempt from

listing

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
sodium nitrite	7632-00-0		1995-01-01

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
sodium nitrite	7632-00-0		1	100 (45,4)

Legend

Clean Air Act

Name of substance	CAS No	Type of registra- tion	Basis for listing	Threshold quantity (lbs)
isobutane	75-28-5	Flammable sub- stance	f	10000

United States: en Page: 15 / 24

[&]quot;1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

Name of substance	CAS No	Type of registra- tion	Basis for listing	Threshold quantity (lbs)
propane	74-98-6	Flammable sub- stance	f	10000

Legend

Flammable gas.

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Water	7732-18-5	solvents	
Silicone compound	63148-62-9	defoamer	
isobutane	75-28-5	propellant	EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B
propane	68476-86-8		EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B
Aminomodified silicone-polyether copolymer	Proprietary	film former	
sodium nitrite	7632-00-0	preservative	
morpholine	110-91-8	corrosion inhibitor	
Polyalkylene Oxide	Proprietary	polymer	
Octamethylcyclotetrasiloxane	556-67-2	emulsifier	Canada PBiTs CECBP - Priority Chemicals EC PBTs

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshol d	De Minimis Con- centration Threshold
sodium nitrite	7632-00-0				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
isobutane		N	
propane	74-98-6	A, O	
propane		N	

United States: en Page: 16 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Revision: 2023-09-11 Version number: GHS 10.2 Replaces version of: 2022-07-05 (GHS 9)

Name of substance	CAS No	References	Remarks
propane		А	gases

Legend

American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

gases N Refers to displacement of air asphyxiation hazard. National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Trans-

0 Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
morpholine	110-91-8		CO F3 R1
isobutane	75-28-5		F4
propane	74-98-6		F4
sodium nitrite	7632-00-0		

Legend

CO Corrosive

F3 Flammable - Third Degree F4 Flammable - Fourth Degree Reactive - First Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
PROPANE, 2-METHYL-	75-28-5	
PROPANE	74-98-6	
NITROUS ACID, SODIUM SALT	7632-00-0	E

Legend

Environmental hazard

- Hazardous Substance List (RI-RTK)

United States: en Page: 17 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

Name of substance	CAS No	References
morpholine	110-91-8	Т, F
morpholine	110-91-8	Т, F
isobutane	106-97-8	T, F
propane	74-98-6	Т
propane	74-98-6	T, F

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
ethylene glycol monomethyl ether	109-86-4		developmental, male
benzene	71-43-2		cancer
benzene	71-43-2		developmental, male

Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	0	no significant risk to health
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

United States: en Page: 18 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Health	0	material that, under emergency conditions, would offer no hazard beyond that of or- dinary combustible material
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	not all ingredients are listed
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed or exempt from listing
VN	NCI	not all ingredients are listed

Legend

AIIC Australian Inventory of Industrial Chemicals CICR

Chemical Inventory and Control Regulation
List of Existing and New Chemical Substances (CSCL-ENCS) **CSCL-ENCS**

DSL Domestic Substances List (DSL)

United States: en Page: 19 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

Legend

ECSI EC Substance Inventory (EINECS, ELINCS, NLP)

IECSC Inventory of Existing Chemical Substances Produced or Imported in China

INSQ National Inventory of Chemical Substances

ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory
NCI National Chemical Inventory
NDSL Non-domestic Substances List (NDSL)
NZIOC New Zealand Inventory of Chemicals

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg. REACH registered substances

TCSI Taiwan Chemical Substance Inventory

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.3		Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance in a concentration of ≥ 0.1%.	yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0.1%.	yes
3.2		Description of the mixture: change in the listing (table)	yes
3.2		Legend: Press. Gas: Press. Gas C: Gas under pressure: compressed gas Press. Gas L: Gas under pressure: liquefied gas Press. Gas R: Gas under pressure: refrigerated li- quefied gas Press. Gas D: Gas under pressure: dissolved gas.	yes
6.2	Environmental precautions: Keep away from drains, surface and ground wa- ter. Retain contaminated washing water and dis- pose of it.	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
8.1		Relevant DNELs of components of the mixture: change in the listing (table)	yes

United States: en Page: 20 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
8.1		Relevant PNECs of components of the mixture: change in the listing (table)	yes
12.1		Aquatic toxicity (acute) of components of the mix- ture: change in the listing (table)	yes
12.1		Aquatic toxicity (chronic) of components of the mixture: change in the listing (table)	yes
12.5	Results of PBT and vPvB assessment: Data are not available.	Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance in a concentration of ≥ 0.1%.	yes
12.6	Endocrine disrupting properties: None of the ingredients are listed.	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0.1%.	yes
15.1	Toxic Substance Control Act (TSCA): all ingredients are listed	Toxic Substance Control Act (TSCA): all ingredients are listed (ACTIVE) or exempt from listing	yes
15.1		Cleaning Product Right to Know Act Substance List (CA-RTK): change in the listing (table)	yes
15.1		Hazardous Substance List (RI-RTK): change in the listing (table)	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2023	From ACGIH®, 2023 TLVs® and BEIs® Book. Copyright 2023. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)

United States: en Page: 21 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

Abbr.	Descriptions of used abbreviations
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance

United States: en Page: 22 / 24





Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

Abbr.	Descriptions of used abbreviations
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NOEC	No Observed Effect Concentration
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
Ox. Sol.	Oxidizing solid
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Press. Gas	Gas under pressure
Press. Gas C	Compressed gas
Press. Gas D	Dissolved gas
Press. Gas L	Liquefied gas
Press. Gas R	Refrigerated liquefied gas
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
sA	Simple asphyxiants
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

United States: en Page: 23 / 24



acc. to 29 CFR 1910.1200 App D

Armor All Extreme Tire Shine - Aerosol

Version number: GHS 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-05 (GHS 9)

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H226	Flammable liquid and vapor.
H272	May intensify fire; oxidizer.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
OSHA002	May displace oxygen and cause rapid suffocation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 24 / 24