



Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

SECTION 1: Identification

1.1 Product identifier

Trade name STP Super Concentrated Fuel Injector Cleaner

Alternative number(s) 071153172418, 071153175631, 071153785779, 071153785755, 071153785946, 067788171117, 067788171193, 067489301448, 067489700517,

067489301295, 067489783534, 067489700531,

067788171117

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc. 25225 Detroit Rd. Westlake OH 44145 United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)

e-mail: Autocare.regulatory@energizer.com

Website: https://data.energizer.com

1.4 Emergency telephone number

Emergency information service

FOR EMERGENCY in USA & Canada CALL +1 800 255-3924 / For International CALL +1 813 248 0585 This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.1I	acute toxicity (inhal.)	4	Acute Tox. 4	H332
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.5	germ cell mutagenicity	1B	Muta. 1B	H340
A.6	carcinogenicity	1A	Carc. 1A	H350
A.7	reproductive toxicity	2	Repr. 2	H361fd
A.8D	specific target organ toxicity - single exposure (narcotic effects, drowsiness)	3	STOT SE 3	H336

United States: en Page: 1 / 28





Version number: 19.0 Revision: 2025-05-20

Replaces version of: 2023-07-19 (18)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.10	aspiration hazard	1	Asp. Tox. 1	H304
B.6	flammable liquid	3	Flam. Liq. 3	H226

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects
The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

H332

GHS02, GHS07, GHS08



- Hazard statements

H226 Flammable liquid and vapor. H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H340 May cause genetic defects.

H350 May cause cancer.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

- Precautionary statements

P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/eye protection/face protection.
P301+P310 If swallowed: Immediately call a poison center/doctor.

P302+P352 If on skin: Wash with plenty of water.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

United States: en Page: 2 / 28





Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

- Precautionary statements

P362 Take off contaminated clothing and wash before reuse.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with national regulations.

- Hazardous ingredients for labelling Distillates (petroleum), hydrodesulfurized middle,

naphthalene, Jet A-1, toluene, benzene

2.3 Other hazards

Hazards not otherwise classified

May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).

Toxic to aquatic life with long lasting effects (GHS category 2: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of \geq 0.1%.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of \geq 0.1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Straight-run Kerosene	CAS No 64741-44-2	10-<25	Acute Tox. 4 / H332 Flam. Liq. 3 / H226	⋄ ••••••••••••••••••••••••••••••••••••
Distillates (petroleum), hy- drodesulfurized middle	CAS No 64742-80-9	10-<25	Acute Tox. 4 / H332 Carc. 1B / H350 Flam. Liq. 3 / H226	
Distillates (petroleum), hy- drodesulfurized light cata- lytic cracked	CAS No 68333-25-5	10 - < 25	Acute Tox. 4 / H332 Carc. 1B / H350 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
Jet A-1	CAS No 8008-20-6	10-<25	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
Kerosine (petroleum), hy- drodesulfurized	CAS No 64742-81-0	5 - < 10	Skin Irrit. 2 / H315 STOT SE 3 / H336	

United States: en Page: 3 / 28





Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
			Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
Solvent naphtha (petro- leum), light arom.	CAS No 64742-95-6	1-<5	Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 1 / H224	
Distillates (petroleum), light hydrocracked	CAS No 64741-77-1	1-<5	Acute Tox. 3 / H331 Carc. 2 / H351 Flam. Liq. 3 / H226	
Polyolefin alkyl phenol al- kyl amine	CAS No Proprietary	1-<5	Skin Irrit. 2 / H315	1
1,2,4 trimethlybenzene	CAS No 95-63-6	1-<5	Acute Tox. 4 / H332 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
naphthalene	CAS No 91-20-3	<1	Acute Tox. 4 / H302 Acute Tox. 1 / H330 Carc. 2 / H351 STOT SE 2 / H371 STOT RE 2 / H373	\$
cumene	CAS No 98-82-8	<1	Carc. 2 / H351 STOT SE 3 / H335 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
2-ethylhexan-1-ol	CAS No 104-76-7	<1	Acute Tox. 2 / H330 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 STOT SE 3 / H335 Flam. Liq. 4 / H227	
benzene	CAS No 71-43-2	<1	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Muta. 1B / H340 Carc. 1A / H350 STOT RE 1 / H372 Asp. Tox. 1 / H304 Flam. Liq. 2 / H225	
ethylbenzene	CAS No 100-41-4	<1	Acute Tox. 4 / H332 Carc. 2 / H351 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	
toluene	CAS No 108-88-3	<1	Acute Tox. 1 / H330 Skin Irrit. 2 / H315 Repr. 2 / H361d STOT SE 3 / H336 STOT RE 2 / H373 Asp. Tox. 1 / H304 Flam. Liq. 2 / H225	

United States: en Page: 4 / 28





Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Cymene	CAS No 25155-15-1	<1	Acute Tox. 3 / H331 Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Repr. 2 / H361 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	

Remarks

For full text of abbreviations: see SECTION 16

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas

United States: en Page: 5 / 28



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner

Version number: 19.0 Revision: 2025-05-20

Replaces version of: 2023-07-19 (18)

such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and

United States: en Page: 6 / 28

Safety Data Sheet acc. to 29 CFR 1910.1200 App D



STP Super Concentrated Fuel Injector Cleaner

Version number: 19.0 Revision: 2025-05-20

Replaces version of: 2023-07-19 (18)

form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapors or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

0 000.												
Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/m ³]	Nota tion	Sourc e	
US	ethylbenzene	100-41-4	PEL (CA)	5	22	30	130				Cal/OS HA PEL	
US	ethylbenzene	100-41-4	REL	100 (10 h)	435 (10 h)	125	545				NIOSH REL	
US	ethylbenzene	100-41-4	TLV®	20							AC- GIH® 2024	
US	ethylbenzene	100-41-4	PEL	100	435						29 CFR 1910.1 000	
US	2-ethyl-1-hexanol	104-76-7	TLV®	5							AC- GIH® 2024	

United States: en Page: 7 / 28





Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/m ³]	Nota tion	Sourc e
US	toluene	108-88-3	REL	100 (10 h)	375 (10 h)	150	560				NIOSH REL
US	toluene	108-88-3	TLV®	20							AC- GIH® 2024
US	toluene	108-88-3	PEL	200		500 (10 min)		300			29 CFR 1910.1 000
US	toluene (toluol)	108-88-3	PEL (CA)	10	37	150	560	500		Н	Cal/OS HA PEL
US	Kerosine - un- specified	64742- 81-0	TLV®		200					vap, Hy- Carb, MX-P, H	AC- GIH® 2024
US	benzene	71-43-2	REL	0.1 (10 h)		1				appx- A	NIOSH REL
US	benzene	71-43-2	PEL (CA)	1		5				Н	Cal/OS HA PEL
US	benzene	71-43-2	TLV®	0.02						Н	AC- GIH® 2024
US	benzene	71-43-2	PEL	1		5				H, i	29 CFR 1910.1 000
US	benzene	71-43-2	PEL	10		50 (10 min)		25		us- pel- z2a	29 CFR 1910.1 000
US	Kerosine (petro- leum)	8008-20- 6	REL		100 (10 h)						NIOSH REL
US	Kerosine (petro- leum) (jet fuels, JP 5)	8008-20- 6	TLV®		200					vap, Hy- Carb, MX-P, H	AC- GIH® 2024
US	naphthalene	91-20-3	REL	10 (10 h)	50 (10 h)	15	75				NIOSH REL
US	naphthalene	91-20-3	PEL	10	50						29 CFR 1910.1 000

United States: en Page: 8 / 28



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner

Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/m ³]	Nota tion	Sourc e
US	naphthalene	91-20-3	PEL (CA)	0.1	0.5					Н	Cal/OS HA PEL
US	naphthalene	91-20-3	TLV®	10						Н	AC- GIH® 2024
US	1,2,4-trimethyl- benzene	95-63-6	REL	25 (10 h)	125 (10 h)						NIOSH REL
US	1,2,4-trimethyl- benzene	95-63-6	TLV®	10							AC- GIH® 2024
US	cumene	98-82-8	TLV®	5							AC- GIH® 2024
US	cumene	98-82-8	REL	50 (10 h)	245 (10 h)					Н	NIOSH REL
US	cumene	98-82-8	PEL	50	245					Н	29 CFR 1910.1 000
US	cumene (isopro- pylbenzene)	98-82-8	PEL (CA)	50	245					Н	Cal/OS HA PEL

Notation

appx-A NIOSH Potential Occupational Carcinogen (Appendix A)

Ceiling-C ceiling value is a limit value above which exposure should not occur

H absorbed through the skin HyCarb calculated as hydrocarbons

i inhalable fraction

MX-P application restricted to conditions where exposure to aerosols is negligible

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period

(unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-

weighted average (unless otherwise specified

us-pel-z2a This standard applies to the industry segments exempt from the 1 ppm 8-hour TWA and 5 ppm STEL of the benzene standard

t 1910.1028.

vap as vapors

United States: en Page: 9 / 28



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner

Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Biological limit values

Country	Name of agent	Parameter	Nota- tion	Identifier	Value	Source
US	ethylbenzene	sum of mandelic acid and phenylglyoxylic acid	crea	BEI®	150 mg/g	ACGIH® 2024
US	toluene	toluene		BEI®	0.02 mg/l	ACGIH® 2024
US	toluene	toluene		BEI®	0.03 mg/l	ACGIH® 2024
US	toluene	o-cresol	hydr, crea	BEI®	0.3 mg/g	ACGIH® 2024
US	benzene	S-phenylmercapturic acid	crea	BEI®	25 μg/g	ACGIH® 2024
US	benzene	t,t-Muconic acid	crea	BEI®	500 μg/g	ACGIH® 2024

Notation

crea creatinine hydr hydrolysis

Relevant DNELs of components

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
Straight-run Ker- osene	64741-44-2	DNEL	16.4 mg/m³	human, inhalat- ory	worker (industry)	chronic - systemic effects
Straight-run Ker- osene	64741-44-2	DNEL	1,501 mg/m³	human, inhalat- ory	worker (industry)	acute - systemic ef- fects
Straight-run Ker- osene	64741-44-2	DNEL	2.91 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Distillates (petro- leum), hydrodesul- furized light catalytic cracked	68333-25-5	DNEL	27.3 mg/m ³	human, inhalat- ory	worker (industry)	chronic - systemic effects
Distillates (petro- leum), hydrodesul- furized light catalytic cracked	68333-25-5	DNEL	2,230 mg/m³	human, inhalat- ory	worker (industry)	acute - systemic ef- fects
Distillates (petro- leum), hydrodesul- furized light catalytic cracked	68333-25-5	DNEL	2.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Distillates (petro- leum), light hydro- cracked	64741-77-1	DNEL	68.34 mg/m³	human, inhalat- ory	worker (industry)	chronic - systemic effects

United States: en Page: 10 / 28



Safety Data Sheet acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner

Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Relevant DNELs of components

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
Distillates (petro- leum), light hydro- cracked	64741-77-1	DNEL	4,288 mg/m³	human, inhalat- ory	worker (industry)	acute - systemic ef- fects
Distillates (petro- leum), light hydro- cracked	64741-77-1	DNEL	2.91 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
1,2,4 trimethlyben- zene	95-63-6	DNEL	100 mg/m ³	human, inhalat- ory	worker (industry)	chronic - systemic effects
1,2,4 trimethlyben- zene	95-63-6	DNEL	100 mg/m ³	human, inhalat- ory	worker (industry)	acute - systemic ef- fects
1,2,4 trimethlyben- zene	95-63-6	DNEL	100 mg/m ³	human, inhalat- ory	worker (industry)	chronic - local ef- fects
1,2,4 trimethlyben- zene	95-63-6	DNEL	100 mg/m ³	human, inhalat- ory	worker (industry)	acute - local effects
1,2,4 trimethlyben- zene	95-63-6	DNEL	16,171 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m³	human, inhalat- ory	worker (industry)	chronic - systemic effects
naphthalene	91-20-3	DNEL	25 mg/m³	human, inhalat- ory	worker (industry)	chronic - local ef- fects
naphthalene	91-20-3	DNEL	3.57 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
cumene	98-82-8	DNEL	100 mg/m ³	human, inhalat- ory	worker (industry)	chronic - systemic effects
cumene	98-82-8	DNEL	250 mg/m ³	human, inhalat- ory	worker (industry)	acute - local effects
cumene	98-82-8	DNEL	15.4 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
2-ethylhexan-1-ol	104-76-7	DNEL	12.8 mg/m³	human, inhalat- ory	worker (industry)	chronic - systemic effects
2-ethylhexan-1-ol	104-76-7	DNEL	53.2 mg/m ³	human, inhalat- ory	worker (industry)	chronic - local ef- fects
2-ethylhexan-1-ol	104-76-7	DNEL	53.2 mg/m ³	human, inhalat- ory	worker (industry)	acute - local effects
2-ethylhexan-1-ol	104-76-7	DNEL	23 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	192 mg/m³	human, inhalat- ory	worker (industry)	chronic - systemic effects
toluene	108-88-3	DNEL	384 mg/m ³	human, inhalat-	worker (industry)	acute - systemic ef-

United States: en Page: 11 / 28



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner

Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Relevant DNELs of components

'											
Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time					
				ory		fects					
toluene	108-88-3	DNEL	192 mg/m³	human, inhalat- ory	worker (industry)	chronic - local ef- fects					
toluene	108-88-3	DNEL	384 mg/m ³	human, inhalat- ory	worker (industry)	acute - local effects					
toluene	108-88-3	DNEL	384 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects					
ethylbenzene	100-41-4	DNEL	77 mg/m³	human, inhalat- ory	worker (industry)	chronic - systemic effects					
ethylbenzene	100-41-4	DNEL	293 mg/m ³	human, inhalat- ory	worker (industry)	acute - local effects					
ethylbenzene	100-41-4	DNEL	180 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects					

Relevant PNECs of components

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
1,2,4 trimethlyben- zene	95-63-6	PNEC	0.12 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
1,2,4 trimethlyben- zene	95-63-6	PNEC	0.12 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
1,2,4 trimethlyben- zene	95-63-6	PNEC	2.41 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
1,2,4 trimethlyben- zene	95-63-6	PNEC	13.56 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
1,2,4 trimethlyben- zene	95-63-6	PNEC	13.56 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
1,2,4 trimethlyben- zene	95-63-6	PNEC	2.34 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
cumene	98-82-8	PNEC	0.035 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
cumene	98-82-8	PNEC	0.004 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
cumene	98-82-8	PNEC	200 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
cumene	98-82-8	PNEC	3.22 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
cumene	98-82-8	PNEC	0.322 ^{mg} / _{kg}	aquatic organ-	marine sediment	short-term (single

United States: en Page: 12 / 28



Safety Data Sheet acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner

Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Relevant PNECs of components

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
				isms		instance)
cumene	98-82-8	PNEC	0.624 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.017 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.002 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	10 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.284 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.028 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
2-ethylhexan-1-ol	104-76-7	PNEC	0.047 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
toluene	108-88-3	PNEC	0.68 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
toluene	108-88-3	PNEC	0.68 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
toluene	108-88-3	PNEC	13.61 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
toluene	108-88-3	PNEC	16.39 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
toluene	108-88-3	PNEC	16.39 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
toluene	108-88-3	PNEC	2.89 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
benzene	71-43-2	PNEC	80 ^{µg} / _I	aquatic organ- isms	freshwater	short-term (single instance)
benzene	71-43-2	PNEC	8 ^{µg} / _I	aquatic organ- isms	marine water	short-term (single instance)
benzene	71-43-2	PNEC	39 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
benzene	71-43-2	PNEC	1.36 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
benzene	71-43-2	PNEC	0.136 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
benzene	71-43-2	PNEC	0.225 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

United States: en Page: 13 / 28





Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Relevant PNECs of components

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
ethylbenzene	100-41-4	PNEC	0.1 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
ethylbenzene	100-41-4	PNEC	0.01 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
ethylbenzene	100-41-4	PNEC	9.6 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
ethylbenzene	100-41-4	PNEC	13.7 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
ethylbenzene	100-41-4	PNEC	1.37 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
ethylbenzene	100-41-4	PNEC	2.68 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	not determined

United States: en Page: 14 / 28





Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	not determined
Flash point	38 °C
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	not determined
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	not determined
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none
Other information	there is no additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

9.2

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

United States: en Page: 15 / 28

Safety Data Sheet acc. to 29 CFR 1910.1200 App D



STP Super Concentrated Fuel Injector Cleaner

Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Harmful if inhaled.

GHS of the United Nations, annex 4: May be harmful in contact with skin.

- Acute toxicity estimate (ATE)

Inhalation: gas 4,031 ppmV/_{4h}
Inhalation: vapor >11.89 mg/₁/₄h

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
Straight-run Kerosene	64741-44-2	dermal	>2,000 ^{mg} / _{kg}
Straight-run Kerosene	64741-44-2	inhalation: vapor	11 ^{mg} / _l /4h
Straight-run Kerosene	64741-44-2	inhalation: dust/mist	>2.53 ^{mg} / _l /4h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	dermal	>2,000 ^{mg} / _{kg}
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	inhalation: vapor	11 ^{mg} / _l /4h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	inhalation: dust/mist	4.6 ^{mg} / _l /4h
Jet A-1	8008-20-6	dermal	>2,000 ^{mg} / _{kg}
Distillates (petroleum), hydrodesulfurized light	68333-25-5	oral	4,660

United States: en Page: 16 / 28





Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
catalytic cracked			mg/ _{kg}
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	dermal	>2,000 ^{mg} / _{kg}
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	inhalation: vapor	11 ^{mg} / _l /4h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	inhalation: dust/mist	4.65 ^{mg} / _l /4h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	dermal	>2,000 ^{mg} / _{kg}
Solvent naphtha (petroleum), light arom.	64742-95-6	dermal	>2,000 ^{mg} / _{kg}
Distillates (petroleum), light hydrocracked	64741-77-1	inhalation: vapor	3.6 ^{mg} / _I /4h
1,2,4 trimethlybenzene	95-63-6	inhalation: vapor	11 ^{mg} / _l /4h
naphthalene	91-20-3	oral	710 ^{mg} / _{kg}
naphthalene	91-20-3	dermal	>2,500 ^{mg} / _{kg}
naphthalene	91-20-3	inhalation: vapor	>0.4 ^{mg} / _l /4h
naphthalene	91-20-3	inhalation: dust/mist	0.005 ^{mg} / _l /4h
2-ethylhexan-1-ol	104-76-7	oral	2,047 ^{mg} / _{kg}
2-ethylhexan-1-ol	104-76-7	inhalation: vapor	>0.89 ^{mg} / _l /4h
toluene	108-88-3	inhalation: gas	7.6 ^{ppmV} / _{4h}
toluene	108-88-3	inhalation: vapor	28.1 ^{mg} / _l /4h
benzene	71-43-2	oral	>2,000 ^{mg} / _{kg}
benzene	71-43-2	inhalation: vapor	43.77 ^{mg} / _l /4h
ethylbenzene	100-41-4	oral	3,500 ^{mg} / _{kg}
ethylbenzene	100-41-4	inhalation: vapor	11 ^{mg} / _l /4h
Cymene	25155-15-1	inhalation: vapor	3 ^{mg} / _l /4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

May cause genetic defects.

Carcinogenicity

May cause cancer.

United States: en Page: 17 / 28





Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
benzene	71-43-2	1	
ethylbenzene	100-41-4	2B	
cumene	98-82-8	2B	
naphthalene	91-20-3	2B	
toluene	108-88-3	3	

<u>Legend</u>

Carcinogenic to humansPossibly carcinogenic to humans

3 Not classifiable as to carcinogenicity in humans

National Toxicology Program (United States): Report on Carcinogens

Name of substance	CAS No	Classification	Number
benzene	71-43-2	Known to be a human carcinogen	1st Report on Carcinogens
cumene	98-82-8	Reasonably anticip- ated to be a human carcinogen	13th Report on Carcinogens
naphthalene	91-20-3	Reasonably anticip- ated to be a human carcinogen	11th Report on Carcinogens

29 CFR 1910/1915/1926 Occupational Safety and Health Standards: Toxic and Hazardous Substances (carcinogens)

Name of substance	CAS No	Type of registration
benzene	71-43-2	GI §1910.1028, SE §1915.1028, CI §1926.1128

Legend

CI §1926.1128 Construction Industry (29 CFR 1926.1128)
GI §1910.1028 General Industry (29 CFR 1910.1028)
SE §1915.1028 Shipyard Employment (29 CFR 1915.1028)

Reproductive toxicity

Suspected of damaging the unborn child. Suspected of damaging fertility.

Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure

Based on available data, the classification criteria are not met.

United States: en Page: 18 / 28





Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Straight-run Kerosene	64741-44-2	LL50	>100 ^{mg} / _l	fish	24 h
Straight-run Kerosene	64741-44-2	EL50	>1,000 ^{mg} / _I	aquatic invertebrates	24 h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	LL50	>100 ^{mg} / _l	fish	24 h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	EL50	>1,000 ^{mg} / _l	aquatic invertebrates	24 h
Jet A-1	8008-20-6	LL50	5 ^{mg} / _l	fish	96 h
Jet A-1	8008-20-6	EL50	1.4 ^{mg} / _I	aquatic invertebrates	48 h
Jet A-1	8008-20-6	LOEL	1 ^{mg} / _l	algae	72 h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	LL50	>0.3 ^{mg} / _I	fish	96 h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	LC50	>0.21 ^{mg} / _l	fish	96 h
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	EL50	0.32 ^{mg} / _l	aquatic invertebrates	48 h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	LL50	2 - 5 ^{mg} / _l	fish	96 h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	EL50	1.4 ^{mg} / _l	aquatic invertebrates	48 h
Kerosine (petroleum), hydrodesulfurized	64742-81-0	LOEL	1 ^{mg} / _l	algae	72 h
Solvent naphtha (pet- roleum), light arom.	64742-95-6	LL50	8.2 ^{mg} / _l	fish	96 h
Solvent naphtha (pet- roleum), light arom.	64742-95-6	EL50	4.5 ^{mg} / _l	aquatic invertebrates	48 h
Distillates (petroleum), light hydrocracked	64741-77-1	LL50	>100 ^{mg} / _l	fish	24 h
Distillates (petroleum),	64741-77-1	EL50	180 ^{mg} / _l	aquatic invertebrates	24 h

United States: en Page: 19 / 28



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner

Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Aquatic toxicity (acute) of components of the mixture

, ,					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
light hydrocracked					
1,2,4 trimethlybenzene	95-63-6	LC50	7.72 ^{mg} / _l	fish	96 h
1,2,4 trimethlybenzene	95-63-6	EC50	2.356 ^{mg} / _l	algae	96 h
naphthalene	91-20-3	LC50	1.6 ^{mg} / _l	fish	96 h
naphthalene	91-20-3	EC50	2.16 ^{mg} / _l	aquatic invertebrates	48 h
cumene	98-82-8	LC50	4.7 ^{mg} / _l	fish	96 h
cumene	98-82-8	EC50	2.14 ^{mg} / _l	aquatic invertebrates	48 h
cumene	98-82-8	ErC50	2.01 ^{mg} / _l	algae	72 h
cumene	98-82-8	NOEC	<2.9 ^{mg} / _l	fish	96 h
2-ethylhexan-1-ol	104-76-7	LC50	17.1 ^{mg} / _l	fish	96 h
2-ethylhexan-1-ol	104-76-7	EC50	39 ^{mg} / _l	aquatic invertebrates	48 h
2-ethylhexan-1-ol	104-76-7	ErC50	16.6 ^{mg} / _l	algae	72 h
2-ethylhexan-1-ol	104-76-7	NOEC	14 ^{mg} / _l	fish	96 h
toluene	108-88-3	LC50	5.5 ^{mg} / _l	fish	96 h
toluene	108-88-3	EC50	84 ^{mg} / _l	microorganisms	24 h
benzene	71-43-2	LC50	5.3 ^{mg} / _l	fish	96 h
benzene	71-43-2	EC50	10 ^{mg} / _l	aquatic invertebrates	24 h
benzene	71-43-2	ErC50	100 ^{mg} / _I	algae	72 h
ethylbenzene	100-41-4	LC50	7 ^{mg} / _l	fish	24 h
ethylbenzene	100-41-4	EC50	2.4 ^{mg} / _l	aquatic invertebrates	48 h
ethylbenzene	100-41-4	NOEC	3.3 ^{mg} / _l	fish	96 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Straight-run Kerosene	64741-44-2	EL50	>1,000 ^{mg} / _l	microorganisms	40 h
Distillates (petroleum), hydrodesulfurized middle	64742-80-9	EL50	>1,000 ^{mg} / _l	microorganisms	40 h
Jet A-1	8008-20-6	EL50	0.89 ^{mg} / _l	aquatic invertebrates	21 d
Jet A-1	8008-20-6	LOEL	1.2 ^{mg} / _l	aquatic invertebrates	21 d
Distillates (petroleum),	68333-25-5	EL50	0.22 ^{mg} / _l	aquatic invertebrates	21 d

United States: en Page: 20 / 28





Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
hydrodesulfurized light catalytic cracked					
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	EC50	0.17 ^{mg} / _l	aquatic invertebrates	21 d
Distillates (petroleum), hydrodesulfurized light catalytic cracked	68333-25-5	NOEC	0.038 ^{mg} / _l	aquatic invertebrates	21 d
Kerosine (petroleum), hydrodesulfurized	64742-81-0	EL50	0.89 ^{mg} / _l	aquatic invertebrates	21 d
Kerosine (petroleum), hydrodesulfurized	64742-81-0	LOEL	1.2 ^{mg} / _l	aquatic invertebrates	21 d
Solvent naphtha (pet- roleum), light arom.	64742-95-6	EL50	10 ^{mg} / _l	fish	21 d
Solvent naphtha (pet- roleum), light arom.	64742-95-6	EC50	15.41 ^{mg} / _l	microorganisms	40 h
Distillates (petroleum), light hydrocracked	64741-77-1	EL50	>1,000 ^{mg} / _l	microorganisms	40 h
naphthalene	91-20-3	EC50	2.96 ^{mg} / _l	algae	4 h
naphthalene	91-20-3	NOEC	0.37 ^{mg} / _l	fish	40 d
naphthalene	91-20-3	LOEC	0.38 ^{mg} / _l	fish	40 d
cumene	98-82-8	EC50	1.5 ^{mg} / _l	aquatic invertebrates	21 d
cumene	98-82-8	LC50	>3 ^{mg} / _l	aquatic invertebrates	21 d
cumene	98-82-8	NOEC	0.38 ^{mg} / _l	fish	28 d
toluene	108-88-3	LC50	3.78 ^{mg} / _l	aquatic invertebrates	2 d
toluene	108-88-3	EC50	3.23 ^{mg} / _l	aquatic invertebrates	7 d
toluene	108-88-3	LOEC	2.77 ^{mg} / _l	fish	40 d
toluene	108-88-3	NOEC	1.39 ^{mg} / _l	fish	40 d
benzene	71-43-2	LOEC	1.6 ^{mg} / _l	fish	32 d
benzene	71-43-2	NOEC	0.8 ^{mg} / _l	fish	32 d
ethylbenzene	100-41-4	LC50	3.6 ^{mg} / _l	aquatic invertebrates	7 d
ethylbenzene	100-41-4	LOEL	1.7 ^{mg} / _l	aquatic invertebrates	7 d
ethylbenzene	100-41-4	NOEC	0.96 ^{mg} / _l	aquatic invertebrates	7 d
ethylbenzene	100-41-4	LOEC	1.7 ^{mg} / _l	aquatic invertebrates	7 d

12.2 Persistence and degradability

United States: en Page: 21 / 28

Safety Data Sheet acc. to 29 CFR 1910.1200 App D



STP Super Concentrated Fuel Injector Cleaner

Revision: 2025-05-20 Version number: 19.0 Replaces version of: 2023-07-19 (18)

Data are not available. 12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of \geq 0.1%.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT **UN 1268** IMDG-Code **UN 1268 ICAO-TI UN 1268**

14.2 UN proper shipping name

DOT Petroleum distillates, n.o.s.

IMDG-Code PETROLEUM DISTILLATES, N.O.S.

ICAO-TI Petroleum distillates, n.o.s.

14.3 Transport hazard class(es)

DOT 3 IMDG-Code 3

United States: en Page: 22 / 28



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner

Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

ICAO-TI 3

14.4 Packing group

DOT III
IMDG-Code III
ICAO-TI III

14.5 Environmental hazards hazardous to the aquatic environment

Environmentally hazardous substance (aquatic prival per A-1 environment)

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

DOT

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration UN1268, Petroleum distillates, n.o.s., (contains:

Straight-run Kerosene, Distillates (petroleum), hydrodesulfurized middle), 3, III, environmentally

hazardous

Reportable quantity (RQ) 5,303 lbs (2,408 kg) (benzene) (xylene)

Danger label(s) 3, fish and tree





Environmental hazards Yes (hazardous to the aquatic environment)

Special provisions (SP) 144, B1, IB3, T4, TP1, TP29

ERG No 128

International Maritime Dangerous Goods Code (IMDG) - Additional information

Particulars in the shipper's declaration UN1268, PETROLEUM DISTILLATES, N.O.S., (con-

tains: Straight-run Kerosene, Distillates (petroleum), hydrodesulfurized middle), 3, III, 38°C c.c.,

MARINE POLLUTANT

Marine pollutant yes (P) (hazardous to the aquatic environment)

Danger label(s) 3, fish and tree



United States: en Page: 23 / 28





Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Special provisions (SP)

Excepted quantities (EQ)

Limited quantities (LQ)

EmS

F-E, S-E

Stowage category

A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Particulars in the shipper's declaration UN1268, Petroleum distillates, n.o.s., (contains:

Straight-run Kerosene, Distillates (petroleum), hy-

drodesulfurized middle), 3, III

Environmental hazards yes (hazardous to the aquatic environment)

Danger label(s) 3



Special provisions (SP)

Excepted quantities (EQ)

Limited quantities (LQ)

A3

E1

10 L

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed or exempt from listing

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
benzene	71-43-2		1987-01-01
ethylbenzene	100-41-4		1987-01-01
cumene	98-82-8		1987-01-01
1,2,4 trimethlybenzene	95-63-6		1987-01-01
naphthalene	91-20-3		1987-01-01

United States: en Page: 24 / 28





Version number: 19.0 Revision: 2025-05-20

Replaces version of: 2023-07-19 (18)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
toluene	108-88-3		1987-01-01

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
benzene	71-43-2	a	1 2 3 4	10 (4,54)
ethylbenzene	100-41-4		1 2 3	1000 (454)
cumene	98-82-8		3 4	5000 (2270)
naphthalene	91-20-3		1 2 3 4	100 (45,4)
toluene	108-88-3		1 2 3 4	1000 (454)

Legend

- 1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act
- 2 "2" indicates that the source is section 307(a) of the Clean Water Act
- 3 "3" indicates that the source is section 112 of the Clean Air Act
- 4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)
- a Benzene was already a CERCLA hazardous substance prior to the CAA Amendments of 1990 and received an adjusted 10-pound RQ based on potential carcinogenicity in an August 14, 1989, final rule (54 FR 33418). The CAA Amendments specify that "benzene (including benzene from gasoline)" is a hazardous air pollutant and, thus, a CERCLA hazardous substance.

Clean Air Act

none of the ingredients are listed

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
benzene	71-43-2		cancer
benzene	71-43-2		developmental, male

United States: en Page: 25 / 28





Version number: 19.0 Revision: 2025-05-20

Replaces version of: 2023-07-19 (18)

Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
ethylbenzene	100-41-4		cancer
cumene	98-82-8		cancer
naphthalene	91-20-3		cancer
toluene	108-88-3		developmental

Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

Name of substance	CAS No	Listed in	Special con- ditions	Excluded transac- tions	DEA - code	Concentra- tion limit
toluene	108-88-3	List II chemicals	SC-6594	excl-trans-12	6594	35% by Weight or Volume

Legend

excl- Excluded transactions: Domestic and import transactions in chemical mixtures that contain acetone, ethyl ether, 2-butanone, trans-12 and/or toluene, unless regulated because of being formulated with other List I or List II chemical(s) above the concentration limit.

List II The term "list II chemical" means a chemical (other than a list I chemical) specified by regulation of the Attorney General as a

chemic- chemical that is used in manufacturing a controlled substance in violation of this subchapter.

SC-6594 Exports only; Limit applies to toluene or any combination of acetone, ethyl ether, 2-butanone, methyl isobutyl ketone, and toluene if present in the mixture by summing the concentrations for each chemical.

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient tem- peratures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

United States: en Page: 26 / 28



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner

Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient tem- peratures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)

<u>Legend</u>

AIIC Australian Inventory of Industrial Chemicals CICR Chemical Inventory and Control Regulation

CSCL-ENCS List of Existing and New Chemical Substances (CSCL-ENCS)

DSL Domestic Substances List (DSL)

ECSI EC Substance Inventory (EINECS, ELINCS, NLP)

IECSC Inventory of Existing Chemical Substances Produced or Imported in China

INSQ National Inventory of Chemical Substances

ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory

NDSL Non-domestic Substances List (NDSL)

NZIOC New Zealand Inventory of Chemicals

United States: en Page: 27 / 28



acc. to 29 CFR 1910.1200 App D

STP Super Concentrated Fuel Injector Cleaner

Version number: 19.0 Revision: 2025-05-20 Replaces version of: 2023-07-19 (18)

Legend

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg. REACH registered substances

TCSI Taiwan Chemical Substance Inventory

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 28 / 28