

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

SECTION 1: Identification

1.1 Product identifier

Trade name STP Tire Fix Sealant and Inflator

Alternative number(s) 071153190610, 071153190658

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

Uses advised against Do not use for squirting or spraying. Do not use

for products which come into direct contact with

the skin.

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc. 25225 Detroit Rd. Westlake OH 44145 United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)

e-mail: Autocare.regulatory@energizer.com

Website: http://data.energizer.com

Energizer Trading Ltd.

Sword House, Totteridge Road, High Wycombe, HP13 6DG, UK

Telephone: +44(0)8000353376

e-mail: ConsumerServiceEU@energizer.com

1.4 Emergency telephone number

Emergency information service

FOR EMERGENCY in USA & Canada CALL +1 800 255-3924 / For International CALL +1 813 248 0585 This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.2	skin corrosion/irritation	1	Skin Corr. 1	H314
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373

United States: en Page: 1 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
B.5	gases under pressure	С	Press. Gas C	H280

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. Delayed or immediate effects can be expected after short or long-term exposure. Contains gas under pressure; may explode if heated.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS04, GHS05, GHS08





- Hazard statements

H280 Contains gas under pressure; may explode if heated.

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P260 Do not breathe dusts or mists.
P280 Wear eye protection/face protection.

P301+P330+P331 If swallowed: Rinse mouth, Do NOT induce vomiting.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.
P321 Specific treatment (see on this label).
P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P501 Dispose of contents/container in accordance with local/regional/national/international regula-

tions.

United States: en Page: 2 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

2.3 Other hazards

Hazards not otherwise classified

Harmful to aquatic life (GHS category 3: aquatic toxicity - acute).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of \geq 0.1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
R-134a	CAS No 811-97-2	25 - < 50	Press. Gas C / H280	\leftrightarrow
1-butoxypropan-2-ol	CAS No 5131-66-8	5 – < 10	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Flam. Liq. 4 / H227	<u>(1)</u>
sodium nitrite	CAS No 7632-00-0	<1	Acute Tox. 3 / H301 Eye Irrit. 2 / H319 Ox. Sol. 2 / H272	

For full text of abbreviations: see SECTION 16.

Legend: Press. Gas

Press. Gas C: Gas under pressure: compressed gas Press. Gas L: Gas under pressure: liquefied gas

Press. Gas R: Gas under pressure: refrigerated liquefied gas

Press. Gas D: Gas under pressure: dissolved gas.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

United States: en Page: 3 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Thaw frosted parts with lukewarm water. Do not rub affected area.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Contact with the product can cause burns and/or frostbite. Contains gas under pressure; may explode if heated.

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

United States: en Page: 4 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Managing of associated risks

- Flammability hazards

Protect from sunlight.

Control of the effects

Protect against external exposure, such as

frost

United States: en Page: 5 / 20

Energizer.

Holdings, Inc.

acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits) this information is not available

Relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time
R-134a	811-97-2	DNEL	13,936 mg/ m³	human, inhalatory	worker (industry)	chronic - systemic effects
1-butoxypropan-2-ol	5131-66-8	DNEL	147 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
1-butoxypropan-2-ol	5131-66-8	DNEL	52 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
sodium nitrite	7632-00-0	DNEL	2 mg/m³	human, inhalatory	worker (industry)	chronic - systemic effects
sodium nitrite	7632-00-0	DNEL	2 mg/m³	human, inhalatory	worker (industry)	acute - systemic ef- fects

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
R-134a	811-97-2	PNEC	0.1 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
R-134a	811-97-2	PNEC	0.01 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
R-134a	811-97-2	PNEC	73 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
R-134a	811-97-2	PNEC	0.75 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	0.525 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)

United States: en Page: 6 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
1-butoxypropan-2-ol	5131-66-8	PNEC	0.052 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	10 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	2.36 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	0.236 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
1-butoxypropan-2-ol	5131-66-8	PNEC	0.16 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.0054 ^{mg} / _l	aquatic organ- isms	water	intermittent re- lease
sodium nitrite	7632-00-0	PNEC	0.005 ^{mg} / _l	aquatic organ- isms	freshwater	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.006 ^{mg} / _l	aquatic organ- isms	marine water	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	21 ^{mg} / _l	aquatic organ- isms	sewage treatment plant (STP)	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.019 ^{mg} / _{kg}	aquatic organ- isms	freshwater sedi- ment	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.022 ^{mg} / _{kg}	aquatic organ- isms	marine sediment	short-term (single instance)
sodium nitrite	7632-00-0	PNEC	0.001 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear protective gloves.

United States: en Page: 7 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

 $Use \ appropriate \ container \ to \ avoid \ environmental \ contamination. \ Keep \ away \ from \ drains, \ surface \ and \ ground \ water.$

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	aerosol (foam aerosol)
Color	not determined
Particle	not relevant (aerosol)
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	100 °C
Flash point	63 °C
Evaporation rate	Not determined
Flammability (solid, gas)	
Vapor pressure	5.74 bar at 20 °C
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available

United States: en Page: 8 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

	Solubility(ies)	not determined
I	Partition coefficient	
	- n-octanol/water (log KOW)	this information is not available

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	>743 °C (auto-ignition temperature (liquids and gases))
Viscosity	not relevant (aerosol)
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Propellant content	32.52 %
Temperature class (USA, acc. to NEC 500)	T1 (maximum permissible surface temperature on the equipment: 450°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Gas under pressure.

If heated:

Danger of explosion, Gas under pressure, Danger of bursting container

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidizers

United States: en Page: 9 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
sodium nitrite	7632-00-0	oral	100 ^{mg} / _{kg}

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

United States: en Page: 10 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
R-134a	811-97-2	LC50	560 ^{mg} / _l	fish	24 h
R-134a	811-97-2	EC50	960 ^{mg} / _l	aquatic invertebrates	24 h
1-butoxypropan-2-ol	5131-66-8	LC50	<1,000 ^{mg} / _l	fish	96 h
1-butoxypropan-2-ol	5131-66-8	EC50	<320 ^{mg} / _I	fish	96 h
1-butoxypropan-2-ol	5131-66-8	NOEC	180 ^{mg} / _l	fish	96 h
sodium nitrite	7632-00-0	LC50	26.3 ^{mg} / _l	fish	96 h
sodium nitrite	7632-00-0	EC50	15.4 ^{mg} / _l	aquatic invertebrates	48 h
sodium nitrite	7632-00-0	ErC50	>100 ^{mg} / _l	algae	72 h
sodium nitrite	7632-00-0	NOEC	100 ^{mg} / _l	algae	72 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of \geq 0.1%.

12.7 Other adverse effects

Data are not available.

United States: en Page: 11 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT UN 1950 IMDG-Code UN 1950 ICAO-TI UN 1950

14.2 UN proper shipping name

DOT Aerosols IMDG-Code AEROSOLS

ICAO-TI Aerosols, non-flammable

14.3 Transport hazard class(es)

DOT 2.2 IMDG-Code 2.2 ICAO-TI 2.2

14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the danger-

ous goods regulations

14.5.1 Additional information LTD QTY

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

United States: en Page: 12 / 20





acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration UN1950, Aerosols, 2.2

Reportable quantity (RQ) 12,300 lbs (5,584 kg) (sodium nitrite) (ammonia ... %)

Danger label(s) 2.2



Special provisions (SP) LTD QTY ERG No 126

International Maritime Dangerous Goods Code (IMDG) - Additional information

Particulars in the shipper's declaration UN1950, AEROSOLS, 2.2

Marine pollutant Danger label(s) 2.2



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959

Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
EmS F-D, S-U

Stowage category -

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Particulars in the shipper's declaration UN1950, Aerosols, non-flammable, 2.2

Danger label(s) 2.2



Special provisions (SP) A98, A145, A167

Excepted quantities (EQ) E0
Limited quantities (LQ) 30 kg

United States: en Page: 13 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed (ACTIVE) or exempt from listing

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
sodium nitrite	7632-00-0		1995-01-01

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
sodium nitrite	7632-00-0		1	100 (45,4)

Legend

Clean Air Act

none of the ingredients are listed

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. \S 802, paragraphs 34 (list I) and 35 (list II)

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

United States: en Page: 14 / 20

[&]quot;1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	1	material that must be preheated before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	1	material that must be preheated before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed

United States: en Page: 15 / 20





acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

Country	Inventory	Status
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
VN	NCI	all ingredients are listed

Legend

AIIC CICR CSCL-ENCS Australian Inventory of Industrial Chemicals

Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS)

DSL Domestic Substances List (DSL)

EC Substance Inventory (EINECS, ELINCS, NLP) **ECSI**

Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances **IECSC**

INSQ

ISHA-ENCS Inventory of Existing and New Chemical Substances (ISHA-ENCS)

KECI Korea Existing Chemicals Inventory NCI National Chemical Inventory

NZIoC New Zealand Inventory of Chemicals Philippine Inventory of Chemicals and Chemical Substances (PICCS) **PICCS**

REACH Reg. REACH registered substances

Taiwan Chemical Substance Inventory TCSI

TSCA **Toxic Substance Control Act**

Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.2		- Precautionary statements: change in the listing (table)	yes
2.3	Other hazards: This material is combustible, but will not ignite readily.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance in a concentration of ≥ 0.1%.	yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0.1%.	yes
3.2		Description of the mixture: change in the listing (table)	yes

United States: en Page: 16 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
3.2		Legend: Press. Gas: Press. Gas C: Gas under pressure: compressed gas Press. Gas L: Gas under pressure: liquefied gas Press. Gas R: Gas under pressure: refrigerated liquefied gas Press. Gas D: Gas under pressure: dissolved gas.	yes
6.2	Environmental precautions: Keep away from drains, surface and ground wa- ter. Retain contaminated washing water and dis- pose of it.	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.	yes
8.1	Control parameters: This information is not available.	Control parameters: Occupational exposure limit values (Workplace Exposure Limits) this information is not available	yes
8.1		Relevant DNELs of components of the mixture: change in the listing (table)	yes
8.1		Relevant PNECs of components of the mixture: change in the listing (table)	yes
12.1		Aquatic toxicity (acute) of components of the mix- ture: change in the listing (table)	yes
12.5	Results of PBT and vPvB assessment: Data are not available.	Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of ≥ 0.1%.	yes
12.6	Endocrine disrupting properties: None of the ingredients are listed.	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0.1%.	yes
15.1	Toxic Substance Control Act (TSCA): all ingredients are listed	Toxic Substance Control Act (TSCA): all ingredients are listed (ACTIVE) or exempt from listing	yes
15.1		National inventories: change in the listing (table)	yes

Abbreviations and acronyms

United States: en Page: 17 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR U.S. Department of Transportation
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
NLP	No-Longer Polymer
NOEC	No Observed Effect Concentration
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition

United States: en Page: 18 / 20



acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

Abbr.	Descriptions of used abbreviations
OSHA	Occupational Safety and Health Administration (United States)
Ox. Sol.	Oxidizing solid
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
Press. Gas	Gas under pressure
Press. Gas C	Compressed gas
Press. Gas D	Dissolved gas
Press. Gas L	Liquefied gas
Press. Gas R	Refrigerated liquefied gas
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H227	Combustible liquid.
H272	May intensify fire; oxidizer.
H280	Contains gas under pressure; may explode if heated.
H301	Toxic if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.

United States: en Page: 19 / 20





acc. to 29 CFR 1910.1200 App D

STP Tire Fix Sealant and Inflator

Version number: 10.2 Revision: 2023-09-11 Replaces version of: 2022-07-13 (9)

Code	Text
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 20 / 20