

acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

SECTION 1: Identification

1.1 Product identifier

Trade name STP AP 75 Penetrant

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc. 25225 Detroit Rd. Westlake OH 44145 United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)

e-mail: Autocare.regulatory@energizer.com

Website: http://data.energizer.com

1.4 Emergency telephone number

Emergency information service

FOR EMERGENCY in USA & Canada CALL +1 800 255-3924 / For International CALL +1 813 248 0585 This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.6	carcinogenicity	1B	Carc. 1B	H350
B.3	flammable aerosol	1	Flam. Aerosol 1	H222
B.5	gases under pressure	С	Press. Gas C	H280

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects Contains gas under pressure; may explode if heated.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

United States: en Page: 1 / 20





STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

- Pictograms

GHS02, GHS04, GHS08



- Hazard statements

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H350 May cause cancer.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P211 Do not spray on an open flame or other ignition source.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 If exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regula-

tions.

- Hazardous ingredients for labelling

Aliphatic Petroleum Distillates

2.3 Other hazards

Hazards not otherwise classified

Harmful to aquatic life (GHS category 3: aquatic toxicity - acute).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of \geq 0.1%.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

United States: en Page: 2 / 20



acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Aliphatic Petroleum Distillates	CAS No 8002-05-9	50 - < 75	Carc. 1B / H350	&
propane	CAS No 74-98-6	10-<25	sA / OSHA002 Flam. Gas 1 / H220 Press. Gas C / H280	&
butane (containing ≥ 0,1 % butadiene (203-450-8))	CAS No 106-97-8	10-<25	Flam. Gas 1 / H220 Press. Gas C / H280	&
Naphtha (petroleum), hy- drotreated heavy	CAS No 64742-48-9	5 – < 10	Asp. Tox. 1 / H304 Flam. Liq. 1 / H224	(3)

For full text of abbreviations: see SECTION 16.

Legend: Press. Gas

Press. Gas C: Gas under pressure: compressed gas

Press. Gas L: Gas under pressure: liquefied gas Press. Gas R: Gas under pressure: refrigerated liquefied gas

Press. Gas D: Gas under pressure: dissolved gas.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Thaw frosted parts with lukewarm water. Do not rub affected area.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

United States: en Page: 3 / 20



acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Contact with the product can cause burns and/or frostbite. Contains gas under pressure; may explode if heated.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

United States: en Page: 4 / 20



acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Flammability hazards

Do not spray on an open flame or other ignition source. Protect from sunlight.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	butane	106-97-8	PEL (CA)	800	1,900						Cal/ OSHA PEL
US	n-butane	106-97-8	REL	800 (10 h)	1,900 (10 h)						NIOSH REL
US	n-butane	106-97-8	TLV®			1,000				Е	AC- GIH® 2023
US	petroleum distil- lates (naphtha) (rubber solvent)	64742- 48-9	PEL	500	2,000						29 CFR 1910.1 000

United States: en Page: 5 / 20



acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	propane	74-98-6	PEL (CA)	1,000	1,800						Cal/ OSHA PEL
US	propane	74-98-6	REL	1,000 (10 h)	1,800 (10 h)						NIOSH REL
US	propane	74-98-6	PEL	1,000	1,800						29 CFR 1910.1 000
US	propane	74-98-6	TLV®							oxy- gen, Simpl e Asp., E	AC- GIH® 2023

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

explosive

oxygen Adequate oxygen delivery to the tissues is necessary for sustaining life

Simple Asp. simple asphyxiants

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period

(unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-

weighted average (unless otherwise specified

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear protective gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

During spraying wear suitable respiratory equipment.

United States: en Page: 6 / 20





STP AP 75 Penetrant

Version number: 3.2 Replaces version of: 2022-07-19 (2) Revision: 2023-09-11

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	aerosol (spray aerosol)
Color	light yellow
Particle	not relevant (aerosol)
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	166 °C
Flash point	42 °C
Evaporation rate	Not determined
Flammability (solid, gas)	flammable aerosol in accordance with GHS criteria

Explosive limits

- Lower explosion limit (LEL)	1.4 vol%
- Upper explosion limit (UEL)	15 vol%
Vapor pressure	≤240 kPa at 37.8 °C
Density	not determined
Vapor density	this information is not available
Relative density	Information on this property is not available
Solubility(ies)	not determined

United States: en Page: 7 / 20



acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	537 °C (auto-ignition temperature (liquids and gases))
Viscosity	not relevant (aerosol)
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Propellant content	33 %
Temperature class (USA, acc. to NEC 500)	T1 (maximum permissible surface temperature on the equipment: 450°C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Gas under pressure. Risk of ignition.

If heated:

Danger of explosion, Gas under pressure, Danger of bursting container

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Do not spray on an open flame or other ignition source. Keep away from heat.

Hints to prevent fire or explosion

Protect from sunlight.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

United States: en Page: 8 / 20



acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

May cause cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
Aliphatic Petroleum Distillates	8002-05-9	3	

Legend

3

Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

United States: en Page: 9 / 20



acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
propane	74-98-6	LC50	49.9 ^{mg} / _l	fish	96 h
propane	74-98-6	EC50	19.37 ^{mg} / _l	algae	96 h
butane (containing ≥ 0,1 % butadiene (203-450-8))	106-97-8	LC50	49.9 ^{mg} / _l	fish	96 h
butane (containing ≥ 0,1 % butadiene (203-450-8))	106-97-8	EC50	19.37 ^{mg} / _l	algae	96 h
Naphtha (petroleum), hydrotreated heavy	64742-48-9	LL50	8.2 ^{mg} / _l	fish	96 h
Naphtha (petroleum), hydrotreated heavy	64742-48-9	EL50	4.5 ^{mg} / _l	aquatic invertebrates	48 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of \geq 0.1%.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of \geq 0.1%.

12.7 Other adverse effects

Data are not available.

United States: en Page: 10 / 20



acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT UN 1950 IMDG-Code UN 1950 ICAO-TI UN 1950

14.2 UN proper shipping name

DOT Aerosols IMDG-Code AEROSOLS

ICAO-TI Aerosols, flammable

14.3 Transport hazard class(es)

DOT 2.1 IMDG-Code 2.1 ICAO-TI 2.1

14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the danger-

ous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

DOT

United States: en Page: 11 / 20





STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration UN1950, Aerosols, 2.1

Danger label(s) 2.1



Special provisions (SP) N82 ERG No 126

International Maritime Dangerous Goods Code (IMDG) - Additional information

Particulars in the shipper's declaration UN1950, AEROSOLS, 2.1, 42°C c.c.

Marine pollutant Danger label(s) 2.1



Special provisions (SP) 63, 190, 277, 327, 344, 381, 959

Excepted quantities (EQ) E0
Limited quantities (LQ) 1 L
EmS F-D, S-U

Stowage category -

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Particulars in the shipper's declaration UN1950, Aerosols, flammable, 2.1

Danger label(s) 2.1



Special provisions (SP) A145, A167

Excepted quantities (EQ) E0
Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

United States: en Page: 12 / 20



acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)
- none of the ingredients are listed
- Specific Toxic Chemical Listings (EPCRA Section 313) none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4) none of the ingredients are listed

Clean Air Act

Name of substance	CAS No	Type of registra- tion	Basis for listing	Threshold quantity (lbs)
propane	74-98-6	Flammable sub- stance	f	10000
butane (containing ≥ 0,1 % butadiene (203- 450-8))	106-97-8	Flammable sub- stance	f	10000

Legend

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Aliphatic Petroleum Distillates	8002-05-9		ATSDR Neurotoxicants Canada PBiTs EC Annex VI CMRs - Cat. 1B
propane	68476-86-8		EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B
butane (containing ≥ 0,1 % butadiene (203- 450-8))	106-97-8		EC Annex VI CMRs - Cat. 1A EC Annex VI CMRs - Cat. 1B
Naphtha (petroleum), hydrotreated heavy	64742-48-9	solvents	Canada PBiTs EC Annex VI CMRs - Cat. 1B

 Toxic or Hazardous Substance List (MA-TURA) none of the ingredients are listed

United States: en Page: 13 / 20

f Flammable gas.





STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
Aliphatic Petroleum Distillates	8002-05-9	A, O, R, T, *	
Naphtha (petroleum), hydrotreated heavy	64742-48-9	A, O	
propane	74-98-6	A, O	
propane		N	
propane		А	gases
butane (containing ≥ 0,1 % butadiene (203- 450-8))		N	

Legend

Substances which are regulated by OSHA as carcinogens; have been categorized by the ACGIH as either "human carcinogens" or "suspect of carcinogenic potential for man"; have been evaluated by the International Agency for Research on Cancer (IARC) and found to be carcinogens or potential carcinogens; or have been listed as a carcinogen or potential carcinogen in the Annual Report on Carcinogens published by the National Toxicology Program (NTP).

American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physic-Α al Agents and Biological Exposure Indices for 1992-93", available from ACGIH

gases

Refers to displacement of air asphyxiation hazard.
National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Trans-

0 Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

International Agency for Research on Cancer (IARC) Monographs on the Evaluation of the Carcinogenic Risks to Humans; Overall Evaluations of Carcinogenicity: An Updating of IARC Monographs Volumes 1 to 42, Supplement 7 (1987). Available from: WHO R Publications Centre USA

National Toxicology Program (NTP) "Fifth Annual Report on Carcinogens," 1989 (NTP 89-239). Order information: (919) 541-3992

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
Aliphatic Petroleum Distillates	8002-05-9		F3
propane	74-98-6		F4
butane (containing ≥ 0,1 % butadiene (203- 450-8))	106-97-8		F4

Legend

F3 Flammable - Third Degree Flammable - Fourth Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

United States: en Page: 14 / 20



acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

Name acc. to inventory	CAS No	Classification
PETROLEUM	8002-05-9	
PROPANE	74-98-6	
BUTANE	106-97-8	

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
Aliphatic Petroleum Distillates	8002-05-9	F
propane	74-98-6	Т
propane	74-98-6	T, F
butane (containing ≥ 0,1 % butadiene (203- 450-8))	106-97-8	T, F

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	0	no significant risk to health
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

United States: en Page: 15 / 20



acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	4	material that rapidly or completely vaporizes at atmospheric pressure and normal ambient temperature or that is readily dispersed in air and burn readily
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
VN	NCI	all ingredients are listed

Legend

AIIC Australian Inventory of Industrial Chemicals CICR

Chemical Inventory and Control Regulation List of Existing and New Chemical Substances (CSCL-ENCS) **CSCL-ENCS**

DSL

ECSI

Domestic Substances List (DSL)
EC Substance Inventory (EINECS, ELINCS, NLP)
Inventory of Existing Chemical Substances Produced or Imported in China National Inventory of Chemical Substances
Korea Existing Chemicals Inventory **IECSC**

INSQ

KECI NCI National Chemical Inventory

United States: en Page: 16 / 20





STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

Legend

NZIOC New Zealand Inventory of Chemicals

PICCS Philippine Inventory of Chemicals and Chemical Substances (PICCS)

REACH Reg. REACH registered substances

TCSI Taiwan Chemical Substance Inventory

TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety- relev- ant
2.2		- Precautionary statements: change in the listing (table)	yes
2.3		Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance in a concentration of ≥ 0.1%.	yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of ≥ 0.1%.	yes
3.2		Legend: Press. Gas: Press. Gas C: Gas under pressure: compressed gas Press. Gas L: Gas under pressure: liquefied gas Press. Gas R: Gas under pressure: refrigerated liquefied gas Press. Gas D: Gas under pressure: dissolved gas.	yes
6.2	Environmental precautions: Keep away from drains, surface and ground wa- ter. Retain contaminated washing water and dis- pose of it.	Environmental precautions: Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
11.1		IARC Monographs on the Evaluation of Carcino- genic Risks to Humans: change in the listing (table)	yes
12.5	Results of PBT and vPvB assessment: Data are not available.	Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of ≥ 0.1%.	yes

United States: en Page: 17 / 20



acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Revision: 2023-09-11

Version number: 3.2 Replaces version of: 2022-07-19 (2)

> Section Former entry (text/value) Actual entry (text/value) Safetyrelevant Endocrine disrupting properties: yes 12.6 Endocrine disrupting properties: None of the ingredients are listed. Does not contain an endocrine disruptor (EDC) in a concentration of \geq 0.1%. 15.1 Cleaning Product Right to Know Act Substance yes List (CA-RTK): change in the listing (table) 15.1 Hazardous Substance List (RI-RTK): yes change in the listing (table) 15.1 National inventories: yes change in the listing (table)

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2023	From ACGIH®, 2023 TLVs® and BEIs® Book. Copyright 2023. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Asp. Tox.	Aspiration hazard
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Carc.	Carcinogenicity
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule

United States: en Page: 18 / 20





STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

Abbr.	Descriptions of used abbreviations
ERG No	Emergency Response Guidebook - Number
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
РВТ	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
ppm	Parts per million
Press. Gas	Gas under pressure
Press. Gas C	Compressed gas
Press. Gas D	Dissolved gas
Press. Gas L	Liquefied gas
Press. Gas R	Refrigerated liquefied gas
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
sA	Simple asphyxiants

United States: en Page: 19 / 20



acc. to 29 CFR 1910.1200 App D

STP AP 75 Penetrant

Version number: 3.2 Revision: 2023-09-11 Replaces version of: 2022-07-19 (2)

Abbr.	Descriptions of used abbreviations
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture. Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H224	Extremely flammable liquid and vapor.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H350	May cause cancer.
OSHA002	May displace oxygen and cause rapid suffocation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 20 / 20