

STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)

Version number: 5.0
Replaces version of: 2023-08-23 (4)

Revision: 2025-05-02

SECTION 1: Identification

1.1 Product identifier

Trade name **STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)**

Alternative number(s) 071153002036, 071153172470

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses General use

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc.
25225 Detroit Rd.
Westlake OH 44145
United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)
e-mail: Autocare.regulatory@energizer.com
Website: <https://data.energizer.com>

Energizer Trading Ltd.
Sword House, Totteridge Road, High Wycombe, HP13 6DG, UK

Telephone: +44(0)8000353376
e-mail: ConsumerServiceEU@energizer.com

1.4 Emergency telephone number

Emergency information service

FOR EMERGENCY in USA & Canada CALL +1 800 255-3924 / For International CALL +1 813 248 0585
This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
A.9	specific target organ toxicity - repeated exposure	2	STOT RE 2	H373

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects
Delayed or immediate effects can be expected after short or long-term exposure.

STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)

Version number: 5.0
Replaces version of: 2023-08-23 (4)

Revision: 2025-05-02

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS05, GHS08



- Hazard statements

H318

Causes serious eye damage.

H373

May cause damage to organs (kidney) through prolonged or repeated exposure (if swallowed).

- Precautionary statements

P260

Do not breathe dust/fume/gas/mist/vapors/spray.

P280

Wear eye protection/face protection.

P305+P351+P338

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310

Immediately call a poison center/doctor.

P501

Dispose of contents/container in accordance with national regulations.

- Hazardous ingredients for labelling

diethylene glycol, Triethylene Glycol Butyl Ether

2.3 Other hazards

Hazards not otherwise classified

May be harmful if swallowed (GHS category 5: acutely toxic - oral).

May be harmful in contact with skin (GHS category 5: acutely toxic - dermal).

May be harmful if inhaled (GHS category 5: acutely toxic - inhalation).

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.


SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures



Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Triethylene Glycol Butyl Ether	CAS No 143-22-6	75 – < 90	Eye Dam. 1 / H318	

STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)

Version number: 5.0
Replaces version of: 2023-08-23 (4)

Revision: 2025-05-02

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
diethylene glycol	CAS No 111-46-6	25 – < 50	Acute Tox. 4 / H302 Acute Tox. 4 / H332 STOT RE 2 / H373	
Diethylene glycol monobutyl ether	CAS No 112-34-5	10 – < 25	Eye Irrit. 2 / H319	

Remarks

For full text of abbreviations: see SECTION 16

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)

Version number: 5.0
Replaces version of: 2023-08-23 (4)

Revision: 2025-05-02

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Use only in well-ventilated areas.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

7.3 Specific end use(s)

See section 16 for a general overview.

STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)

Version number: 5.0
Replaces version of: 2023-08-23 (4)

Revision: 2025-05-02

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Coun-try	Name of agent	CAS No	Iden-tifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceil-ing-C [ppm]	Ceil-ing-C [mg/m ³]	Nota-tion	Sour-ce
US	diethylene glycol monobutyl ether	112-34-5	TLV®	10						iv	AC-GIH® 2024

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur

iv inhalable fraction and vapor

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components

Name of sub-stance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Triethylene Glycol Butyl Ether	143-22-6	DNEL	195 mg/m ³	human, inhalat-ory	worker (industry)	chronic - systemic effects
Triethylene Glycol Butyl Ether	143-22-6	DNEL	208 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
diethylene glycol	111-46-6	DNEL	44 mg/m ³	human, inhalat-ory	worker (industry)	chronic - systemic effects
diethylene glycol	111-46-6	DNEL	60 mg/m ³	human, inhalat-ory	worker (industry)	chronic - local ef-fects
diethylene glycol	111-46-6	DNEL	43 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Diethylene glycol monobutyl ether	112-34-5	DNEL	67.5 mg/m ³	human, inhalat-ory	worker (industry)	chronic - systemic effects
Diethylene glycol monobutyl ether	112-34-5	DNEL	83 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Diethylene glycol monobutyl ether	112-34-5	DNEL	67.5 mg/m ³	human, inhalat-ory	worker (industry)	chronic - local ef-fects
Diethylene glycol monobutyl ether	112-34-5	DNEL	101.2 mg/m ³	human, inhalat-ory	worker (industry)	acute - local effects

STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)

Version number: 5.0
Replaces version of: 2023-08-23 (4)

Revision: 2025-05-02

Relevant PNECs of components						
Name of sub-stance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Triethylene Glycol Butyl Ether	143-22-6	PNEC	2 mg/l	aquatic organ-isms	freshwater	short-term (single instance)
Triethylene Glycol Butyl Ether	143-22-6	PNEC	0.2 mg/l	aquatic organ-isms	marine water	short-term (single instance)
Triethylene Glycol Butyl Ether	143-22-6	PNEC	200 mg/l	aquatic organ-isms	sewage treatment plant (STP)	short-term (single instance)
Triethylene Glycol Butyl Ether	143-22-6	PNEC	7.7 mg/kg	aquatic organ-isms	freshwater sedi-ment	short-term (single instance)
Triethylene Glycol Butyl Ether	143-22-6	PNEC	0.77 mg/kg	aquatic organ-isms	marine sediment	short-term (single instance)
Triethylene Glycol Butyl Ether	143-22-6	PNEC	0.47 mg/kg	terrestrial organ-isms	soil	short-term (single instance)
diethylene glycol	111-46-6	PNEC	10 mg/l	aquatic organ-isms	freshwater	short-term (single instance)
diethylene glycol	111-46-6	PNEC	1 mg/l	aquatic organ-isms	marine water	short-term (single instance)
diethylene glycol	111-46-6	PNEC	199.5 mg/l	aquatic organ-isms	sewage treatment plant (STP)	short-term (single instance)
diethylene glycol	111-46-6	PNEC	20.9 mg/kg	aquatic organ-isms	freshwater sedi-ment	short-term (single instance)
diethylene glycol	111-46-6	PNEC	2.09 mg/kg	aquatic organ-isms	marine sediment	short-term (single instance)
diethylene glycol	111-46-6	PNEC	1.53 mg/kg	terrestrial organ-isms	soil	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	200 mg/l	aquatic organ-isms	sewage treatment plant (STP)	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	1.1 mg/l	aquatic organ-isms	freshwater	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	0.11 mg/l	aquatic organ-isms	marine water	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	4.4 mg/kg	aquatic organ-isms	freshwater sedi-ment	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	0.44 mg/kg	aquatic organ-isms	marine sediment	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	0.32 mg/kg	terrestrial organ-isms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls
General ventilation.

STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)

Version number: 5.0
Replaces version of: 2023-08-23 (4)

Revision: 2025-05-02

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	not determined
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	231 °C at 1 atm
Flash point	>93 °C
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	0.022 mmHg at 25 °C
Density	not determined
Vapor density	this information is not available

STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)

Version number: 5.0
Replaces version of: 2023-08-23 (4)

Revision: 2025-05-02

Relative density	Information on this property is not available
Solubility(ies)	not determined

Partition coefficient

- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	202 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

9.2 Other information

Temperature class (USA, acc. to NEC 500)	T3 (maximum permissible surface temperature on the equipment: 200°C)
--	--

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials".

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

There are no specific conditions known which have to be avoided.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)

Version number: 5.0

Replaces version of: 2023-08-23 (4)

Revision: 2025-05-02

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Based on available data, the classification criteria are not met.

GHS of the United Nations, annex 4: May be harmful if swallowed, in contact with skin or if inhaled.

Acute toxicity estimate (ATE) of components

Name of substance	CAS No	Exposure route	ATE
Triethylene Glycol Butyl Ether	143-22-6	dermal	3,540 mg/kg
diethylene glycol	111-46-6	oral	1,120 mg/kg
diethylene glycol	111-46-6	inhalation: vapor	11 mg/l/4h
diethylene glycol	111-46-6	inhalation: dust/mist	>4.6 mg/l/4h
Diethylene glycol monobutyl ether	112-34-5	oral	2,410 mg/kg
Diethylene glycol monobutyl ether	112-34-5	dermal	2,764 mg/kg

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure

May cause damage to organs (kidney) through prolonged or repeated exposure (if swallowed).

Hazard category	Target organ	Exposure route
2	kidney	if swallowed

Aspiration hazard

Based on available data, the classification criteria are not met.

STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)

Version number: 5.0
Replaces version of: 2023-08-23 (4)

Revision: 2025-05-02

SECTION 12: Ecological information

12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance at a concentration of $\geq 0.1\%$.

12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (ED) in a concentration of $\geq 0.1\%$.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	not subject to transport regulations
14.2	UN proper shipping name	not relevant
14.3	Transport hazard class(es)	none
14.4	Packing group	not assigned
14.5	Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6	Special precautions for user	
	There is no additional information.	



STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)

Version number: 5.0
Replaces version of: 2023-08-23 (4)

Revision: 2025-05-02

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA)

all ingredients are listed or exempt from listing

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure

STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)

Version number: 5.0
Replaces version of: 2023-08-23 (4)

Revision: 2025-05-02

Category	Rating	Description
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

STP Heavy Duty Brake Fluid DOT 3 - bottle (After 5-1-2021)

Version number: 5.0
Replaces version of: 2023-08-23 (4)

Revision: 2025-05-02

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.
Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG).
Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.
Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.