



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

### SECTION 1: Identification

#### 1.1 Product identifier

Trade name **Eagle One Etching Mag Wheel Cleaner**  
Alternative number(s) 079933998661, 012844040227

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Consumer uses  
Uses advised against Do not use for squirting or spraying. Do not use for products which come into direct contact with the skin.

#### 1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc.  
25225 Detroit Rd.  
Westlake OH 44145  
United States  
  
Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)  
e-mail: Autocare.regulatory@energizer.com  
Website: <http://data.energizer.com>

#### 1.4 Emergency telephone number

Emergency information service  
FOR EMERGENCY in USA & Canada CALL +1 800 255-3924 / For International CALL +1 813 248 0585  
This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

### SECTION 2: Hazard(s) identification

#### 2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	1	Skin Corr. 1	H314
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
B.6	flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Skin corrosion produces an irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis. The product is combustible and can be ignited by potential ignition sources.

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

### 2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word                      danger

- Pictograms

GHS05



- Hazard statements

H227                      Combustible liquid.

H314                      Causes severe skin burns and eye damage.

- Precautionary statements

P101                      If medical advice is needed, have product container or label at hand.

P102                      Keep out of reach of children.

P103                      Read label before use.

P210                      Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P260                      Do not breathe dusts or mists.

P280                      Wear protective gloves/eye protection/face protection.

P301+P330+P331                      If swallowed: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353                      If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340                      If inhaled: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338                      If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310                      Immediately call a poison center/doctor.

P321                      Specific treatment (see on this label).

P363                      Wash contaminated clothing before reuse.

P370+P378                      In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P235                      Store in a well-ventilated place. Keep cool.

P405                      Store locked up.

P501                      Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling                      ammonium bifluoride, n-[3-(Dimethylnitrotroryl)propyl]dodecanamide

### 2.3 Other hazards

Hazards not otherwise classified

Contains epoxy constituents. May produce an allergic reaction.

Results of PBT and vPvB assessment

Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0.1\%$ .

Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0.1\%$ .

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11






### SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not relevant (mixture)

#### 3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
C9-C11 Alcohol Ethoxylate	CAS No 68439-46-3 160901-09-7	1 – < 5	Eye Irrit. 2B / H320	
n-[3-(Dimethylnitro)propyl]dodecanamide	CAS No 61792-31-2	1 – < 5	Acute Tox. 4 / H302 Skin Irrit. 2 / H315 Eye Dam. 1 / H318	 
Diethylene glycol monobutyl ether	CAS No 112-34-5	1 – < 5	Eye Irrit. 2 / H319	
ammonium bifluoride	CAS No 1341-49-7	< 1	Acute Tox. 3 / H301 Skin Corr. 1B / H314 Eye Dam. 1 / H318	 

For full text of abbreviations: see SECTION 16.

### SECTION 4: First-aid measures

#### 4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.



## Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

### Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

### SECTION 5: Fire-fighting measures

#### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO<sub>x</sub>), Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

### SECTION 6: Accidental release measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder



## Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

### Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

- Handling of incompatible substances or mixtures

- Keep away from

Caustic solutions

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

#### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

frost



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

- Ventilation requirements  
Use local and general ventilation. Ground/bond container and receiving equipment.
- Packaging compatibilities  
Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

### 7.3 Specific end use(s)

See section 16 for a general overview.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m <sup>3</sup> ]	STEL [ppm]	STEL [mg/m <sup>3</sup> ]	Ceiling-C [ppm]	Ceiling-C [mg/m <sup>3</sup> ]	Notation	Source
US	diethylene glycol monobutyl ether	112-34-5	TLV®	10						iv	AC-GIH® 2023

#### Notation

Ceiling-C

ceiling value is a limit value above which exposure should not occur

iv

inhalable fraction and vapor

STEL

short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA

time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

#### Relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	DNEL	294 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	DNEL	2,080 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Diethylene glycol monobutyl ether	112-34-5	DNEL	67.5 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
Diethylene glycol monobutyl ether	112-34-5	DNEL	83 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Diethylene glycol monobutyl ether	112-34-5	DNEL	67.5 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - local effects



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

### Relevant DNELs of components of the mixture

Name of sub-stance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Diethylene glycol monobutyl ether	112-34-5	DNEL	101.2 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects
ammonium bifluoride	1341-49-7	DNEL	2.3 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects
ammonium bifluoride	1341-49-7	DNEL	3.8 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects

### Relevant PNECs of components of the mixture

Name of sub-stance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	PNEC	0.011 mg/l	aquatic organisms	freshwater	short-term (single instance)
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	PNEC	0.001 mg/l	aquatic organisms	marine water	short-term (single instance)
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	PNEC	0.074 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	PNEC	0.007 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	PNEC	0.009 mg/kg	terrestrial organisms	soil	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	200 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	1.1 mg/l	aquatic organisms	freshwater	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	0.11 mg/l	aquatic organisms	marine water	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	4.4 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	0.44 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Diethylene glycol monobutyl ether	112-34-5	PNEC	0.32 mg/kg	terrestrial organisms	soil	short-term (single instance)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

### Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
ammonium bifluoride	1341-49-7	PNEC	1.3 mg/l	aquatic organisms	freshwater	short-term (single instance)
ammonium bifluoride	1341-49-7	PNEC	76 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
ammonium bifluoride	1341-49-7	PNEC	22 mg/kg	terrestrial organisms	soil	short-term (single instance)

## 8.2 Exposure controls

### Appropriate engineering controls

General ventilation.

### Individual protection measures (personal protective equipment)

#### Eye/face protection

Wear eye/face protection.

#### Skin protection

##### - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

##### - Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### Appearance





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

Physical state	liquid
Color	colorless
Particle	not relevant (liquid)
Odor	Pleasant

### Other safety parameters

pH (value)	2 – 3
Melting point/freezing point	not determined
Initial boiling point and boiling range	90.6 °C at 1,013 hPa
Flash point	70 °C
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	0.022 mmHg at 25 °C
Density	1.1 g/cm <sup>3</sup> at 20 °C
Vapor density	this information is not available
Relative density	1.1 at 20 °C (air = 1)
Solubility(ies)	not determined

### Partition coefficient

- n-octanol/water (log KOW)	this information is not available
-----------------------------	-----------------------------------

### Auto-ignition temperature

Viscosity	not determined
Explosive properties	none
Oxidizing properties	none

### 9.2

#### Other information

there is no additional information



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

#### 10.2 Chemical stability

See below "Conditions to avoid".

#### 10.3 Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### 10.5 Incompatible materials

Oxidizers

#### 10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

### SECTION 11: Toxicological information

#### 11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

#### Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
n-[3-(Dimethylnitro)propyl]dodecanamide	61792-31-2	oral	500 mg/kg
ammonium bifluoride	1341-49-7	oral	130 mg/kg



## Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

### Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

#### Skin corrosion/irritation

Causes severe skin burns and eye damage.

#### Serious eye damage/eye irritation

Causes serious eye damage.

#### Respiratory or skin sensitization

Contains epoxy constituents. May produce an allergic reaction.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

#### Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

## SECTION 12: Ecological information

### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

### 12.2 Persistence and degradability

Data are not available.

### 12.3 Bioaccumulative potential

Data are not available.

### 12.4 Mobility in soil

Data are not available.

### 12.5 Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of  $\geq 0.1\%$ .

### 12.6 Endocrine disrupting properties

Does not contain an endocrine disruptor (EDC) in a concentration of  $\geq 0.1\%$ .



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

### 12.7 Other adverse effects

Data are not available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

## SECTION 14: Transport information

### 14.1 UN number

DOT	UN 3264
IMDG-Code	UN 3264
ICAO-TI	UN 3264

### 14.2 UN proper shipping name

DOT	Corrosive liquid, acidic, inorganic, n.o.s.
IMDG-Code	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.
ICAO-TI	Corrosive liquid, acidic, inorganic, n.o.s.
Technical name (hazardous ingredients)	ammonium bifluoride, isopropyl alcohol

### 14.3 Transport hazard class(es)

DOT	8
IMDG-Code	8
ICAO-TI	8

### 14.4 Packing group

DOT	III
IMDG-Code	III
ICAO-TI	III

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)


Revision: 2023-09-11

- |  |   |
|--|---|
| <b>14.5 Environmental hazards</b>                          | non-environmentally hazardous acc. to the dangerous goods regulations |
| <b>14.6 Special precautions for user</b>                   | There is no additional information.                                   |
| <b>14.7 Transport in bulk according to IMO instruments</b> | The cargo is not intended to be carried in bulk.                      |


### Information for each of the UN Model Regulations

DOT

#### Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Particulars in the shipper's declaration	UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (ammonium bifluoride, isopropyl alcohol, solution), 8, III
Reportable quantity (RQ)	14,925 lbs (6,776 kg) (ammonium bifluoride) (prop-2-yn-1-ol)
Danger label(s)	8
	
Special provisions (SP)	IB3, T7, TP1, TP28
ERG No	154

#### International Maritime Dangerous Goods Code (IMDG) - Additional information

Particulars in the shipper's declaration	UN3264, CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S., (ammonium bifluoride, isopropyl alcohol, solution), 8, III
Marine pollutant	-
Danger label(s)	8
	
Special provisions (SP)	223, 274
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-B
Stowage category	A
Segregation group	1 - Acids



# Safety Data Sheet


acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

### International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Particulars in the shipper's declaration	UN3264, Corrosive liquid, acidic, inorganic, n.o.s., (ammonium bifluoride, isopropyl alcohol, solution), 8, III
Danger label(s)	8
	
Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	1 L

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations specific for the product in question

##### National regulations (United States)

##### Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
ammonium bifluoride	1341-49-7		1	100 (45,4)

##### Legend

1 "1" indicates that the statutory source is section 311(b)(2) of the Clean Water Act

##### Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Water	7732-18-5	solvents	
Water	7732-18-5	solvents	
C9-C11 Alcohol Ethoxylate	68439-46-3 160901-09-7	surfactant	
n-[3-(Dimethylnitro)propyl]dodecanamide	61792-31-2	surfactant	
Diethylene glycol monobutyl ether		solvents	CA TACs
ammonium bifluoride	1341-49-7	cleaning agent	
Myristamidopropylamine oxide	67806-10-4	surfactant	
Quaternary coco alkylamine ethoxylate	61791-10-4	emulsifier	



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

Name of substance	CAS No	Functionality	Authoritative Lists
isopropyl alcohol	67-63-0	solvents	OEHHA RELs
2-aminoethanol	141-43-5	pH Adjuster	
prop-2-yn-1-ol	107-19-7	fragrance	

### - Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
ammonium bifluoride	1341-49-7				1.0 %
ammonium bifluoride	7664-41-7				1.0 %
Diethylene glycol monobutyl ether		1022			1.0 %

### - Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
ammonium bifluoride	1341-49-7		CO
Diethylene glycol monobutyl ether			

#### Legend

CO Corrosive

### - Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
AMMONIUM FLUORIDE ((NH <sub>4</sub> )(HF <sub>2</sub> ))	1341-49-7	E
GLYCOL ETHERS		E

#### Legend

E Environmental hazard

### California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

#### Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
1,4-dioxane	123-91-1		cancer
ethylene oxide	75-21-8		cancer



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

### Proposition 65 List of chemicals

Name acc. to inventory	CAS No	Remarks	Type of the toxicity
ethylene oxide	75-21-8		female
ethylene oxide	75-21-8		developmental, male

### Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

none of the ingredients are listed

### Industry or sector specific available guidance(s)

#### NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

#### NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		





# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

### National inventories

Country	Inventory	Status
AU	AIIC	all ingredients are listed
CA	DSL	all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	not all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	all ingredients are listed
US	TSCA	all ingredients are listed (ACTIVE)
VN	NCI	all ingredients are listed

#### Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NCI	National Chemical Inventory
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

### 15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

### SECTION 16: Other information, including date of preparation or last revision

#### Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2		- Precautionary statements: change in the listing (table)	yes
2.3	Other hazards: This material is combustible, but will not ignite readily.	Other hazards	yes
2.3		Results of PBT and vPvB assessment: Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$ .	yes
2.3		Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$ .	yes
8.1		Occupational exposure limit values (Workplace Exposure Limits): change in the listing (table)	yes
8.1		Relevant DNELs of components of the mixture: change in the listing (table)	yes
8.1		Relevant PNECs of components of the mixture: change in the listing (table)	yes
11.1		Acute toxicity estimate (ATE) of components of the mixture: change in the listing (table)	yes
12.5	Results of PBT and vPvB assessment: Data are not available.	Results of PBT and vPvB assessment: According to the results of its assessment, this substance is not a PBT or a vPvB. Does not contain a PBT-/vPvB-substance in a concentration of $\geq 0.1\%$ .	yes
12.6	Endocrine disrupting properties: None of the ingredients are listed.	Endocrine disrupting properties: Does not contain an endocrine disruptor (EDC) in a concentration of $\geq 0.1\%$ .	yes
15.1		National inventories: change in the listing (table)	yes

#### Abbreviations and acronyms



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

Abbr.	Descriptions of used abbreviations
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2023	From ACGIH®, 2023 TLVs® and BEIs® Book. Copyright 2023. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: <a href="http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement">http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement</a>
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EmS	Emergency Schedule
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LHS	Lower hazard substance
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)



# Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

## Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

Abbr.	Descriptions of used abbreviations
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

### Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

### Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H227	Combustible liquid.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H320	Causes eye irritation.



## Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

### Eagle One Etching Mag Wheel Cleaner

Version number: GHS 11.1  
Replaces version of: 2022-07-11 (GHS 10)

Revision: 2023-09-11

---

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.