Safety Data Sheet

### Acetone-d6

According to Regulation (EC) No. 1907/2006 (REACH)

Date of compilation: 2022-09-19

Version number: GHS 1.2

1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Zeochem AG

Switzerland

Identification of the substance Registration number (REACH) CAS number Alternative name(s) Acetone-d6

this information is not available 666-52-4 propan-2-one, propanone

### **1.2** Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

general use

Telephone: +41 44 922 93 93: e-Mail: Info@zeochem.com / info@zeochem.ch: Website: Https://www.zeochem.com:

#### 1.4 Emergency telephone number

Joweid 5, CH-8630 Rüti

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Details of the supplier of the safety data sheet

#### Classification according to Regulation (EC) No 1272/2008 (CLP)

Section	Hazard class	Category	Hazard class and cat- egory	Hazard state- ment
2.6	flammable liquid	2	Flam. Liq. 2	H225
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319
3.8D	specific target organ toxicity - single exposure (narcotic ef- fects, drowsiness)	3	STOT SE 3	H336

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.



Safety Data Sheet

Chemistry. Pure. Efficient.

## Acetone-d6

According to Regulation (EC) No. 1907/2006 (REACH)

Date of compilation: 2022-09-19

#### Version number: GHS 1.2

#### 2.2 Label elements

### Labelling according to Regulation (EC) No 1272/2008 (CLP)

#### - Signal word danger

#### 2.2.1.2 Pictograms

GHS02, GHS07					
Hazard statements					
H225	highly flammable liquid and vapour				
H319	causes serious eye irritation				
H336	may cause drowsiness or dizziness				

Precautionary statements						
P210	keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking					
P261	avoid breathing dust/fume/gas/mist/vapours/spray					
P312	call a POISON CENTRE/doctor if you feel unwell					
P370+P378	in case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish					
P403+P233	store in a well-ventilated place. Keep container tightly closed					
P403+P235	store in a well-ventilated place. Keep cool					
P501	dispose of contents/container in accordance with local/regional/national/international regulations					

- Supplemental hazard information EUH066 Repeated exposure may cause skin dryness or cracking.

#### 2.3 Other hazards

#### Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

### **SECTION 3: Composition/information on ingredients**

#### 3.1 Substances

Name of substance	Acetone-d6		
Identifiers			
CAS No	666-52-4		
EC No	211-563-9		
Molecular formula	C3D6O		
Molar mass	64.1 <sup>g</sup> / <sub>mol</sub>		



Safety Data Sheet

### Acetone-d6

According to Regulation (EC) No. 1907/2006 (REACH)

Date of compilation: 2022-09-19

Version number: GHS 1.2

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

#### General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

#### Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

#### Following skin contact

Wash with plenty of soap and water.

#### Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

#### Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Narcotic effects.

#### 4.3 Indication of any immediate medical attention and special treatment needed

none

#### **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO2)

#### Unsuitable extinguishing media

Water jet

#### 5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

#### Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO2)

#### 5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.



## Safety Data Sheet

Acetone-d6

According to Regulation (EC) No. 1907/2006 (REACH)

Date of compilation: 2022-09-19

#### Version number: GHS 1.2

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders Wear breathing apparatus if exposed to vapours/dust/spray/gases.

#### 6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

#### 6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

#### Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

#### 6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

#### **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Recommendations

Store in a dry place.

#### - Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

#### - Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

#### Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.





Version number: GHS 1.2

## Acetone-d6

According to Regulation (EC) No. 1907/2006 (REACH)

Date of compilation: 2022-09-19

#### 7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

#### - Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

#### - Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

#### - Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to ADR) may be used.

#### 7.3 Specific end use(s)

See section 16 for a general overview.

#### **SECTION 8: Exposure controls/personal protection**

#### 8.1 **Control parameters**

Occup	Occupational exposure limit values (Workplace Exposure Limits)									
Coun- try	Name of agent	CAS No	Identi- fier	TWA [ppm]	TWA [mg/m³]	STEL [ppm]	STEL [mg/m³]	Ceiling-C [mg/m³]	Nota- tion	Source
DE	acetone	67-64-1	MAK	500	1,200	1,000	2,400			DFG
DE	acetone	67-64-1	AGW	500	1,200	1,000	2,400		Y	TRGS 900
ES	acetone	67-64-1	VLA	500	1,210					INSHT
EU	acetone	67-64-1	IOELV	500	1,210					2000/ 39/EC
FR	acetone	67-64-1	VME	500	1,210	1,000	2,420			INRS
IT	acetone	67-64-1	VLEP	500	1,210					G.U. n. 218 - Al- legato XXXVIII

Notation

V

Ceiling-C ceiling value is a limit value above which exposure should not occur

a risk of developmental toxicity does not need to be expected if the occupational exposure limit value and the biological limit value (BGW) are adhered to



STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

## Safety Data Sheet

Acetone-d6

According to Regulation (EC) No. 1907/2006 (REACH)

Version number: GHS 1.2

Date of compilation: 2022-09-19

Biol	ogical	limit	val	lues
	ogical	mmu	va	lues

Country	Name of agent	Parameter	Notation	Identifier	Value	Source
DE	Aceton	Aceton		BAT	50 mg/l	DFG
DE	Aceton	Aceton		BAT (BAR)	2.5 mg/l	DFG
DE	acetone	acetone		BLV	80 mg/l	TRGS 903
ES	acetone	acetone		VLB	50 mg/l	INSHT

#### Human health values

Relevant DNELs and other threshold levels								
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time				
DNEL	1,210 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	chronic - systemic effects				
DNEL	2,420 mg/m <sup>3</sup>	human, inhalatory	worker (industry)	acute - local effects				
DNEL	186 mg/kg bw/ day	human, dermal	worker (industry)	chronic - systemic effects				

#### **Environmental values**

Relevant	Relevant PNECs and other threshold levels							
Endpoint	Threshold level	Organism	Environmental compartment	Exposure time				
PNEC	10.6 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	freshwater	short-term (single instance)				
PNEC	1.06 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	marine water	short-term (single instance)				
PNEC	100 <sup>mg</sup> / <sub>l</sub>	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)				
PNEC	30.4 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	freshwater sediment	short-term (single instance)				
PNEC	3.04 <sup>mg</sup> / <sub>kg</sub>	aquatic organisms	marine sediment	short-term (single instance)				
PNEC	29.5 <sup>mg</sup> / <sub>kg</sub>	terrestrial organisms	soil	short-term (single instance)				

#### 8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

#### Eye/face protection

Wear eye/face protection.





## Acetone-d6

According to Regulation (EC) No. 1907/2006 (REACH)

Date of compilation: 2022-09-19

Version number: GHS 1.2

Skin protection - Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leaktightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Type of material

Nitrile IIR: isobutene-isoprene (butyl) rubber

- Breakthrough times of the glove material

>30 minutes (permeation: level 2)

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

#### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

#### Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

#### SECTION 9: Physical and chemical properties

#### 9.1 Information on basic physical and chemical properties

Physical state	liquid
Colour	colourless
Odour	characteristic
Melting point/freezing point	-94.8 °C
Boiling point or initial boiling point and boiling range	56.1 °C
Flammability	flammable liquid in accordance with GHS criteria
Lower and upper explosion limit	not determined
Flash point	-17 °C closed cup
Auto-ignition temperature	465 °C (ECHA)
Decomposition temperature	not relevant
pH (value)	5 – 6 (20 °C)
Kinematic viscosity	not determined





Acetone-d6

According to Regulation (EC) No. 1907/2006 (REACH)

Version number: GHS 1.2

Date of compilation: 2022-09-19

Solubility(ies)					
Water solubility	miscible in any proportion				

#### Partition coefficient

Partition coefficient n-octanol/water (log value)	-0.23 (ECHA)
---	--------------

	`	Vapour pressure	240 hPa at 20 °C
--	---	-----------------	------------------

#### Density and/or relative density

Density	0.88 <sup>g</sup> / <sub>cm³</sub> at 25 °C
Relative vapour density	information on this property is not available

Particle characteristics	not relevant (liquid)
--------------------------	-----------------------

#### 9.2 Other information

Information with regard to physical hazard classes	there is no additional information
--	------------------------------------

Other safety characteristics

Miscibility	Completely miscible with water.
Surface tension	38.1 <sup>mN</sup> / <sub>m</sub> (-91.1 °С) (есна)
Refractive index	1.36 (20 °C) ((lit.))
Temperature class (EU, acc. to ATEX)	T1 (maximum permissible surface temperature on the equip- ment: 450°C)

#### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". It's a reactive substance. The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

#### 10.2 Chemical stability

See below "Conditions to avoid".





Acetone-d6

According to Regulation (EC) No. 1907/2006 (REACH)

Date of compilation: 2022-09-19

#### **10.3** Possibility of hazardous reactions

No known hazardous reactions.

#### 10.4 Conditions to avoid

Version number: GHS 1.2

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

#### Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

#### **10.5** Incompatible materials

Oxidisers

#### **10.6** Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

#### **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Classification according to GHS (1272/2008/EC, CLP)

Acute toxicity

Shall not be classified as acutely toxic.

#### Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

#### Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

#### Carcinogenicity

Shall not be classified as carcinogenic.

#### Reproductive toxicity

Shall not be classified as a reproductive toxicant.

#### Specific target organ toxicity - single exposure

May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

#### Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

#### Other information

Repeated exposure may cause skin dryness or cracking.





Chemistry. Pure. Efficient.

## Acetone-d6

According to Regulation (EC) No. 1907/2006 (REACH)

Version number: GHS 1.2

Date of compilation: 2022-09-19

### **11.2** Information on other hazards

There is no additional information.

#### **SECTION 12: Ecological information**

#### 12.1 Toxicity

Shall not be classified as hazardous to the aquatic environment.

#### 12.2 Persistence and degradability

Process of degradability		
Process	Degradation rate	Time
carbon dioxide generation	90.9 %	28 d

#### 12.3 Bioaccumulative potential

Data are not available.

n-octanol/water (log KOW)	-0.23 (ECHA)
BOD5/COD	963.54166667

#### 12.4 Mobility in soil

Henry's law constant	2.93 <sup>Pa m³</sup> / <sub>mol</sub> at 25 °C
----------------------	---

#### 12.5 Results of PBT and vPvB assessment

Data are not available.

#### 12.6 Endocrine disrupting properties

Not listed.

#### 12.7 Other adverse effects

Data are not available.

#### **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

#### Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

#### Waste treatment of containers/packagings

It is a dangerous waste; only packagings which are approved (e.g. acc. to ADR) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

#### Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

page 10 / 13



## Safety Data Sheet

Version number: GHS 1.2


Chemistry. Pure. Efficient.

## Acetone-d6

According to Regulation (EC) No. 1907/2006 (REACH)

Date of compilation: 2022-09-19

version	Date of compliation. 2022-09-1		
SECT	ION 14: Transport information		
14.1	UN number or ID number		
	ADR/RID/ADN	UN 1090	
	IMDG-Code	UN 1090	
	ICAO-TI	UN 1090	
14.2	UN proper shipping name		
	ADR/RID/ADN	ACETONE	
	IMDG-Code	ACETONE	
	ICAO-TI	Acetone	
14.3	Transport hazard class(es)		
	ADR/RID/ADN	3	
	IMDG-Code	3	
	ICAO-TI	3	
14.4	Packing group		
	ADR/RID/ADN	II	
	IMDG-Code	II	
	ICAO-TI	II	
14.5	Environmental hazards	non-environmentally hazardous acc. to the dan- gerous goods regulations	
14.6	<b>Special precautions for user</b> Provisions for dangerous goods (ADR) should be complied	d within the premises.	
14.7	<b>Maritime transport in bulk according to IMO instruments</b> The cargo is not intended to be carried in bulk.		
	Information for each of the UN Model Regulations		
	Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) - Additional information		
	Classification code	F1	
	Danger label(s)	3	



Hazard identification No

page 11 / 13

E2

1 L

D/E

33

2





#### Chemistry. Pure. Efficient.

Acetone-d6

## Safety Data Sheet

Version number: GHS 1.2

According to Regulation (EC) No. 1907/2006 (REACH)

Date of compilation: 2022-09-19

	•
International Maritime Dangerous Goods Cod	e (IMDG) - Additional information
Marine pollutant	-
Danger label(s)	3
Special provisions (SP)	-
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L
EmS	F-E, S-D
Stowage category	E
International Civil Aviation Organization (ICA	O-IATA/DGR) - Additional information
Danger label(s)	3
Excepted quantities (EQ)	E2
Limited quantities (LQ)	1 L

#### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture Relevant provisions of the European Union (EU) Restrictions according to REACH, Annex XVII

Dangerous substances with restrictions (REACH, Annex XVII)			
Name of substance	Name acc. to inventory	CAS No	No
Acetone-d6	this product meets the criteria for classification in accordance with Regulation No 1272/2008/EC		3
Acetone-d6	flammable / pyrophoric		40
Acetone-d6	substances in tattoo inks and permanent make- up		75

### List of substances subject to authorisation (REACH, Annex XIV) / SVHC - candidate list

not listed

Directive on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS)

not listed

## Regulation concerning the establishment of a European Pollutant Release and Transfer Register (PRTR)

not listed





Chemistry. Pure. Efficient.

## Safety Data Sheet

Acetone-d6

According to Regulation (EC) No. 1907/2006 (REACH)

Version number: GHS 1.2

Date of compilation: 2022-09-19

#### Water Framework Directive (WFD)

not listed

#### **Regulation on persistent organic pollutants (POP)**

Not listed.

#### **National inventories**

Country	Inventory	Status
EU	REACH Reg.	substance is listed
US	TSCA	substance is listed
Logond		

Legend

REACH Reg. REACH registered substances TSCA Toxic Substance Control Act

#### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

#### **SECTION 16: Other information**

#### Key literature references and sources for data

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures. Regulation (EC) No. 1907/2006 (REACH), amended by 2020/878/EU.

Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

#### List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H225	Highly flammable liquid and vapour.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

#### Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

