

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Identification of the substance	p-Xylene-d10
CAS number	41051-88-1
Alternative name(s)	1,4-xylene-d10

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	the product is intended for research, analysis and scientific education scientific research and development product and process oriented research and development laboratory and analytical use laboratory chemical
HS code	2845.90.

1.3 Details of the supplier of the safety data sheet

Zeochem AG Joweid 5, CH-8630 Rüti Switzerland	Telephone: +41 44 922 93 93 e-Mail: info@zeochem.com / info@zeochem.ch Website: https://www.zeochem.com
---	---

1.4 Emergency telephone number

Poison centre		
Country	Name	Telephone
international	CHEMTREC (worldwide)	+1 703 741 5500 - 24h/7d (toll free)
Switzerland	Toxzentrum Zürich / Tox. Info Suisse	+41 44 251 51 51 / CH: 145 - 24h/7d

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification acc. to GHS

Section	Hazard class	Category	Hazard class and category	Hazard statement
2.6	flammable liquid	3	Flam. Liq. 3	H226
3.10	acute toxicity (oral)	5	Acute Tox. 5	H303
3.1D	acute toxicity (dermal)	4	Acute Tox. 4	H312
3.1I	acute toxicity (inhal.)	4	Acute Tox. 4	H332
3.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
3.3	serious eye damage/eye irritation	2	Eye Irrit. 2	H319

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

Section	Hazard class	Category	Hazard class and category	Hazard statement
3.8R	specific target organ toxicity - single exposure (respiratory tract irritation)	3	STOT SE 3	H335
3.10	aspiration hazard	1	Asp. Tox. 1	H304
4.1A	hazardous to the aquatic environment - acute hazard	2	Aquatic Acute 2	H401
4.1C	hazardous to the aquatic environment - chronic hazard	3	Aquatic Chronic 3	H412

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources. Spillage and fire water can cause pollution of watercourses.

2.2 Label elements

Labelling

- Signal word danger

2.2.1.2 Pictograms

GHS02, GHS07, GHS08	
---------------------	--

Hazard statements	
H226	flammable liquid and vapour
H303	may be harmful if swallowed
H304	may be fatal if swallowed and enters airways
H312+H332	harmful in contact with skin or if inhaled
H315	causes skin irritation
H319	causes serious eye irritation
H335	may cause respiratory irritation
H411	toxic to aquatic life with long lasting effects

Precautionary statements	
P210	keep away from heat/sparks/open flames/hot surfaces. No smoking
P240	ground/bond container and receiving equipment
P241	use explosion-proof electrical/ventilating/lighting equipment
P242	use only non-sparking tools
P243	take precautionary measures against static discharge
P261	avoid breathing dust/fume/gas/mist/vapours/spray

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

Precautionary statements	
P271	use only outdoors or in a well-ventilated area
P273	avoid release to the environment
P280	wear protective gloves/protective clothing/eye protection/face protection
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor
P302+P352	IF ON SKIN: Wash with plenty of water
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312	call a POISON CENTER/doctor if you feel unwell
P321	specific treatment (see on this label)
P331	do NOT induce vomiting
P362+P364	take off contaminated clothing and wash it before reuse
P370+P378	in case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish
P403+P233	store in a well-ventilated place. Keep container tightly closed
P403+P235	store in a well-ventilated place. Keep cool
P405	store locked up
P501	dispose of contents/container in accordance with local/regional/national/international regulations

2.3 Other hazards

Results of PBT and vPvB assessment

According to the results of its assessment, this substance is not a PBT or a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	p-xylene-d10
Identifiers	
CAS No	41051-88-1
Molecular formula	C8D10
Molar mass	116 g/mol

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

SECTION 4: First aid measures**4.1 Description of first aid measures**

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapour-air mixture. Solvent vapours are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Co-ordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapours/dust/spray/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling**

Recommendations

Store in a dry place.

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapours are heavier than air, spread along floors and form explosive mixtures with air. Vapours may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Keep any substance that emits harmful vapours or gases in a place that allows these to be permanently extracted. Use local and general ventilation. Ground/bond container and receiving equipment.

- Packaging compatibilities

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
CN	xylene, mixture of isomers	106-42-3	OEL		50		100				GBZ 2.1

Notation

Ceiling-C

STEL

TWA

ceiling value is a limit value above which exposure should not occur
short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours
time-weighted average (unless otherwise specified)

Human health values

Relevant DNELs and other threshold levels				
Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
DNEL	221 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
DNEL	442 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
DNEL	212 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

Environmental values

Relevant PNECs and other threshold levels				
Endpoint	Threshold level	Organism	Environmental compartment	Exposure time
PNEC	0.044 mg/l	aquatic organisms	freshwater	short-term (single instance)
PNEC	0.004 mg/l	aquatic organisms	marine water	short-term (single instance)
PNEC	1.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
PNEC	2.52 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
PNEC	0.252 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
PNEC	0.852 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Type of material

Nitrile

IIR: isobutene-isoprene (butyl) rubber

- Breakthrough times of the glove material

>30 minutes (permeation: level 2)

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Colour	not determined
Particle	not relevant (liquid)
Odour	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	-25.2 °C at 1,013 hPa
Initial boiling point and boiling range	135 – 138 °C at 1,013 hPa
Flash point	32 °C at 1,013 hPa (closed cup)
Evaporation rate	not determined
Flammability (solid, gas)	not relevant, (fluid)

Explosive limits

- Lower explosion limit (LEL)	0.9 vol%
- Upper explosion limit (UEL)	6.7 vol%

Vapour pressure	0.194 PSI at 90 °F
Density	0.95 g/cm ³
Vapour density	this information is not available

Solubility(ies)

- Water solubility	170 mg/l at 25 °C
--------------------	-------------------

Partition coefficient

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

- n-octanol/water (log KOW)	3.12 (pH value: 7, 20 °C) (ECHA)
- Soil organic carbon/water (log KOC)	2.73 (ECHA)
Auto-ignition temperature	463 °C at 1,013 hPa (ECHA)

Viscosity

- Kinematic viscosity	0.8 mm ² /s at 25 °C
- Dynamic viscosity	0.76 mPa s at 25 °C
Explosive properties	none
Oxidising properties	none

9.2 Other information

Surface tension	29.8 mN/m (25 °C) (ECHA)
Refractive index	1.49 (20 °C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". It's a reactive substance. The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidisers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Classification acc. to GHS

Acute toxicity

May be harmful if swallowed. Harmful in contact with skin. Harmful if inhaled.

- Acute toxicity estimate (ATE)

Oral 3,523 mg/kg
Inhalation: vapour 11 mg/l/4h

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute)			
Endpoint	Value	Species	Exposure time
LC50	7.6 mg/l	fish	96 h
LL50	5.55 mg/l	fish	72 h
ErC50	4.7 mg/l	algae	72 h

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

Aquatic toxicity (acute)			
Endpoint	Value	Species	Exposure time
EC50	4.9 mg/l	algae	72 h
EL50	5.74 mg/l	algae	72 h

Aquatic toxicity (chronic)			
Endpoint	Value	Species	Exposure time
EL50	2.9 mg/l	aquatic invertebrates	21 d
ErC50	4.36 mg/l	algae	73 h
EC50	2.2 mg/l	algae	73 h

12.2 Persistence and degradability

Biodegradation

The substance is readily biodegradable.

Process of degradability		
Process	Degradation rate	Time
oxygen depletion	94 %	28 d

12.3 Bioaccumulative potential

Data are not available.

n-octanol/water (log KOW)	3.12 (pH value: 7, 20 °C) (ECHA)
BCF	>5.5 – <12.2 (ECHA)

12.4 Mobility in soil

Henry's law constant	623 Pa m ³ /mol at 25 °C
The Organic Carbon normalised adsorption coefficient	2.73 (ECHA)

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

Not listed.

12.7 Other adverse effects

Data are not available.

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packagings

Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

UN RTDG	UN 1307
IMDG-Code	UN 1307
ICAO-TI	UN 1307

14.2 UN proper shipping name

UN RTDG	XYLENES
IMDG-Code	XYLENES
ICAO-TI	Xylenes

14.3 Transport hazard class(es)

UN RTDG	3
IMDG-Code	3
ICAO-TI	3

14.4 Packing group

UN RTDG	III
IMDG-Code	III
ICAO-TI	III

14.5 Environmental hazards

non-environmentally hazardous acc. to the dangerous goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to IMO instruments

The cargo is not intended to be carried in bulk.

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

Information for each of the UN Model Regulations

Transport information - National regulations - Additional information (UN RTDG)

UN number	1307
Class	3
Packing group	III
Danger label(s)	3



Special provisions (SP)	223 (UN RTDG)
Excepted quantities (EQ)	E1 (UN RTDG)
Limited quantities (LQ)	5 L (UN RTDG)

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	-
Danger label(s)	3



Special provisions (SP)	223
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-E, S-D
Stowage category	A

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Danger label(s)	3
-----------------	---



Special provisions (SP)	A3
Excepted quantities (EQ)	E1
Limited quantities (LQ)	10 L

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

There is no additional information.

National inventories

Country	Inventory	Status
EU	REACH Reg.	substance is listed
US	TSCA	substance is listed

Legend

REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
1.2	Relevant identified uses: the product is intended for research, analysis and scientific education scientific research and development product and process orientated research and development laboratory and analytical use laboratory chemical	Relevant identified uses: the product is intended for research, analysis and scientific education scientific research and development product and process oriented research and development laboratory and analytical use laboratory chemical	yes
1.4		Poison centre: change in the listing (table)	yes
9.1	Kinematic viscosity: 0.864 mm ² /s at 25 °C	Kinematic viscosity: 0.8 mm ² /s at 25 °C	yes

Key literature references and sources for data

General Rule for Classification and Hazard Communication of Chemicals (National Standard GB 13690). National Standard: Safety Data Sheet for Chemical Products - Content and Order of Sections. GB/T 16483. National Standard: Guidance on Compilation of Safety Data Sheet for Chemical Products. GB/T 17519.

UN Recommendations on the Transport of Dangerous Good. International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

List of relevant phrases (code and full text as stated in section 2 and 3)

Safety Data Sheet

p-xylene-d10

Classification acc. to 29 CFR 1910.1200

Version number: GHS 2.0
Replaces version of: 10.12.2021 (GHS 1)

Revision: 01.02.2023

Code	Text
H226	Flammable liquid and vapour.
H303	May be harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H401	Toxic to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.